

RZ03-1A3-D005 Information



For Reference Only

Part Number RZ03-1A3-D005

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RZ03-1A3-D005 Specifications

Manufacturer Part Number RZ03-1A3-D005 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RZ, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RZ03-1A3-D005
Package-SeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series RZ, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 84mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current84mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 84mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Series	RZ, SCHRACK
Coil Current84mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Coil Current	84mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style 3.5 VDC 3.5 VDC 6ms Fundamental Style Through Hole PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time 6ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.5 VDC
Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	6ms
Termination Style PC Pin	Features	Insulation - Class F
•	Mounting Type	Through Hole
Domont owners	Termination Style	PC Pin
Report errors?		Report errors?

RZ03-1A3-D005 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RZ03-1A3-D005 Payment Methods



















RZ03-1A3-D005 Shipping Methods













If you have any question about RZ03-1A3-D005, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com