

RZ03-1A4-D009 Information



For Reference Only

Part Number RZ03-1A4-D009

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 9V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RZ03-1A4-D009 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package - Series RZ, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 6.3 VDC
Category Relays Power Relays, Over 2 Amps Package - Series RZ, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 4400VAC - Max Turn On Voltage (Max) 6.3 VDC
Package - Series RZ, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage (Max) 6.3 VDC
Package - Series RZ, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Series RZ, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Coil Voltage 9VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 6.3 VDC
Turn On Voltage (Max) 6.3 VDC
-
Trum Off Values (Min)
Turn Off Voltage (Min) 0.9 VDC
Operate Time 8ms
Release Time 6ms
Features Insulation - Class F
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

RZ03-1A4-D009 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RZ03-1A4-D009 Payment Methods



















RZ03-1A4-D009 Shipping Methods













If you have any question about RZ03-1A4-D009, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com