

### S1-2404D Information



For Reference Only

Part NumberS1-2404DManufacturerCynergy 3CategoryRelays

Signal Relays, Up to 2 Amps

**Description** RELAY REED 4KV SPST 24V SIP W/DI

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **S1-2404D Specifications**

Manufacturer Part Number         \$1-2404D           Manufacturer         Cynergy 3           Category         Relays           Package         -           Series         \$1           Relay Type         Reed           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         24VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         1A           Switching Voltage         300VAC, 350VDC - Max           Turn On Voltage (Max)         16 VDC           Turn Off Voltage (Min)         1.25 VDC           Operate Time         Ims           Release Time         0.5ms           Features         Diode           Mounting Type         Through Hole		
Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         S1           Relay Type         Reed           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         24VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         1A           Switching Voltage         300VAC, 350VDC - Max           Turn On Voltage (Max)         16 VDC           Turn Off Voltage (Min)         1.25 VDC           Operate Time         1ms           Release Time         0.5ms           Features         Diode	Manufacturer Part Number	S1-2404D
Package         -           Series         \$1           Relay Type         Reed           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         24VDC           Contact Form         \$P\$T-NO (1 Form A)           Contact Rating (Current)         1A           Switching Voltage         300VAC, 350VDC - Max           Turn On Voltage (Max)         16 VDC           Turn Off Voltage (Min)         1.25 VDC           Operate Time         1ms           Release Time         0.5ms           Features         Diode	Manufacturer	Cynergy 3
Package - Series S1 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) 1.25 VDC Operate Time Ims Release Time 0.5ms Features Diode	Category	Relays
Series         S1           Relay Type         Reed           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         24VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         1A           Switching Voltage         300VAC, 350VDC - Max           Turn On Voltage (Max)         16 VDC           Turn Off Voltage (Min)         1.25 VDC           Operate Time         1ms           Release Time         0.5ms           Features         Diode		Signal Relays, Up to 2 Amps
Relay Type  Coil Type  Non Latching  Coil Current  24mA  Coil Voltage  24VDC  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  1A  Switching Voltage  300VAC, 350VDC - Max  Turn On Voltage (Max)  16 VDC  Turn Off Voltage (Min)  1.25 VDC  Operate Time  Ims  Release Time  0.5ms  Features  Diode	Package	-
Coil Type	Series	S1
Coil Current 24mA Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 16 VDC Turn Off Voltage (Min) 1.25 VDC Operate Time 1ms Release Time 0.5ms Features Diode	Relay Type	Reed
Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 1A  Switching Voltage 300VAC, 350VDC - Max  Turn On Voltage (Max) 16 VDC  Turn Off Voltage (Min) 1.25 VDC  Operate Time 1ms  Release Time 0.5ms  Features Diode	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current)  Switching Voltage 300VAC, 350VDC - Max  Turn On Voltage (Max)  16 VDC  Turn Off Voltage (Min)  1.25 VDC  Operate Time  Ims  Release Time  0.5ms  Features  Diode	Coil Current	24mA
Contact Rating (Current)  Switching Voltage  300VAC, 350VDC - Max  Turn On Voltage (Max)  16 VDC  Turn Off Voltage (Min)  1.25 VDC  Operate Time  1ms  Release Time  0.5ms  Features  Diode	Coil Voltage	24VDC
Switching Voltage 300VAC, 350VDC - Max  Turn On Voltage (Max) 16 VDC  Turn Off Voltage (Min) 1.25 VDC  Operate Time 1ms  Release Time 0.5ms  Features Diode	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  16 VDC  Turn Off Voltage (Min)  1.25 VDC  Operate Time  1ms  Release Time  0.5ms  Features  Diode	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  Release Time  0.5ms  Features  Diode	Switching Voltage	300VAC, 350VDC - Max
Operate Time1msRelease Time0.5msFeaturesDiode	Turn On Voltage (Max)	16 VDC
Release Time 0.5ms Features Diode	Turn Off Voltage (Min)	1.25 VDC
Features Diode	Operate Time	1ms
	Release Time	0.5ms
Mounting Type Through Hole	Features	Diode
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

### S1-2404D Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## S1-2404D Payment Methods



















### S1-2404D Shipping Methods













If you have any question about S1-2404D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com