

**S1008R-391J Information**


For Reference Only

**Part Number** [S1008R-391J](#)  
**Manufacturer** API Delevan Inc.  
**Category** Inductors, Coils, Chokes  
[Fixed Inductors](#)  
**Description** FIXED IND 390NH 840MA 160 MOHM  
**Package** 1008 (2520 Metric)  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**S1008R-391J Specifications**

Manufacturer Part Number	<a href="#">S1008R-391J</a>
Manufacturer	API Delevan Inc.
Category	Inductors, Coils, Chokes <a href="#">Fixed Inductors</a>
Package	1008 (2520 Metric)
Series	S1008R
Type	-
Material - Core	Ferrite
Inductance	390nH
Tolerance	±5%
Current Rating	840mA
Current - Saturation	-
Shielding	Shielded
DC Resistance (DCR)	160 mOhm Max
Q @ Freq	40 @ 25MHz
Frequency - Self Resonant	278MHz
Ratings	-
Operating Temperature	-55°C ~ 125°C
Frequency - Test	25MHz
Features	-
Mounting Type	Surface Mount
Package / Case	1008 (2520 Metric)
Supplier Device Package	1008 (2520 Metric)
Size / Dimension	0.115" L x 0.105" W (2.92mm x 2.66mm)

Height - Seated (Max)

0.095" (2.41mm)

[Report errors?](#)

## S1008R-391J Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## S1008R-391J Payment Methods



## S1008R-391J Shipping Methods



If you have any question about S1008R-391J, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)