


# S121J33SL0N6UJ5R

### S121J33SL0N6UJ5R Information

Heisener.com	Part Number	S121J33SL0N6UJ5R	
	Manufacturer	Vishay BC Components	
	Category	Capacitors Ceramic Capacitors	
	Description	CAP CER 120PF 1KV SL RADIAL	
	Package	Radial, Disc	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
· · · · · · · · · · · · · · · · · · ·		E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

## S121J33SL0N6UJ5R Specifications

Manufacturer Part Number S121J3SL0N6UJ5R   Manufacturer Vishay BC Components   Category Capacitors   Category Ceramic Capacitors   Package Radial, Disc   Series S   Capacitance 120pF   Tolerance ±5%   Voltage - Rated 1000V (1kV)   Temperature Coefficient SL   Operating Temperature -55°C ~ 125°C   Features -   Applications General Purpose   Failure Rate -   Mounting Type Matial, Disc   Size / Dimension 0.335° Dia (8.50mm)   Height - Seated (Max) -   Thickness (Max) -   Lead Spacing 0.197" (5.00mm)	-	
CategoryCapacitorsPackageRadial, DiscPackageRadial, DiscSeriesSCapacitance120pFTolerance±5%Voltage - Rated1000V (1kV)Temperature CoefficientSLOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335° Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)	Manufacturer Part Number	S121J33SL0N6UJ5R
Ceranic CapacitorsPackageRadial, DiscSeriesSCapacitance120pFTolerance±5%Voltage - Rated1000V (1kV)Temperature CoefficientSLOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335° Dia (8.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197° (5.00mm)Lead StyleStraight	Manufacturer	Vishay BC Components
PackageRdial, DiscSeriesSCapacitance120pFTolerance±5%Voltage - Rated1000V (1KV)Temperature CoefficientSLOperating Temperature-55°C ~ 125°CFeatures-ApplicationsGeneral PurposeFailure Rate-Mounting TypeShoge AllPackage / CaseRadia, DiscSize / Dimension0.335° Dia (8.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197° (3.00mm)Lead StyleStraight	Category	Capacitors
SeriesSCapacitance120pFTolerance±5%Voltage - Rated1000V (1kV)Temperature CoefficientSLOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.335° Dia (8.50mm)Height - Seated (Max)0.492° (12.50mm)Thickness (Max)-Lead Spacing0.197° (5.00mm)Lead StyleStraight		Ceramic Capacitors
Capacitance120pFTolerance±5%Voltage - Rated1000V (1kV)Temperature CoefficientSLOperating Temperature-5°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.335° Dia (8.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197° (5.00mm)Lead StyleStraight	Package	Radial, Disc
Tolerance±5%Voltage - Rated1000V (1kV)Temperature CoefficientSLOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Series	S
Voltage - Rated1000V (1kV)Temperature CoefficientSLOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.492" (12.50mm)Height - Seated (Max)-Thickness (Max)0.197" (5.00mm)Lead SpacingStraightLead StyleStraight	Capacitance	120pF
Temperature CoefficientSLOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Voltage - Rated	1000V (1kV)
Fratures-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)0.197" (5.00mm)Lead SpacingStraight	Temperature Coefficient	SL
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.335" Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension0.335" Dia (8.50mm)Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Mounting Type	Through Hole
Height - Seated (Max)0.492" (12.50mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Package / Case	Radial, Disc
Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Size / Dimension	0.335" Dia (8.50mm)
Lead Spacing0.197" (5.00mm)Lead StyleStraight	Height - Seated (Max)	0.492" (12.50mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Straight
		Report errors?

#### S121J33SL0N6UJ5R Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### S121J33SL0N6UJ5R Payment Methods





If you have any question about S121J33SL0N6UJ5R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com