

S2-24EU Information



For Reference Only

Part Number S2-24EU
Manufacturer Cynergy 3
Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 1A 24V UL

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S2-24EU Specifications

ManufacturerCynergy 3CategoryRelaysFackage-SeriesS2Relay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)1ASwitching Voltage300VAC, 350VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)4 VDCOperate Time1msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StyleAxial		
Category Relays Package - Series S2 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style Axial	Manufacturer Part Number	S2-24EU
Package - Series S2 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style Acxial	Manufacturer	Cynergy 3
Package-SeriesS2Relay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)1ASwitching Voltage300VAC, 350VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)4 VDCOperate TimeImsRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StyleAxial	Category	Relays
SeriesS2Relay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)1ASwitching Voltage300VAC, 350VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)4 VDCOperate TimeImsRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StyleAxial		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)1ASwitching Voltage300VAC, 350VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)4 VDCOperate TimeImsRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StyleAxial	Package	-
Coil TypeNon LatchingCoil Current24mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)1ASwitching Voltage300VAC, 350VDC - MaxTurn On Voltage (Max)19 VDCTurn Off Voltage (Min)4 VDCOperate Time1msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StyleAxial	Series	S2
Coil Current 24mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style Axial	Relay Type	Reed
Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style Axial	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time Ims Release Time 0.5ms Features - Mounting Type Through Hole Termination Style	Coil Current	24mA
Contact Rating (Current) Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	24VDC
Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style Axial	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 19 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style Axial	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time Ims Release Time 0.5ms Features Mounting Type Through Hole Termination Style Axial	Switching Voltage	300VAC, 350VDC - Max
Operate Time1msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StyleAxial	Turn On Voltage (Max)	19 VDC
Release Time 0.5ms Features - Mounting Type Through Hole Termination Style Axial	Turn Off Voltage (Min)	4 VDC
Features - Mounting Type Through Hole Termination Style Axial	Operate Time	1ms
Mounting Type Through Hole Termination Style Axial	Release Time	0.5ms
Termination Style Axial	Features	-
	Mounting Type	Through Hole
	Termination Style	Axial
Report errors?		Report errors?

S2-24EU Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S2-24EU Payment Methods





















S2-24EU Shipping Methods













If you have any question about S2-24EU, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com