

S28AW Information



For Reference Only

Part Number S28AW

Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 15A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S28AW Specifications

Manufacturer Part Number \$28AW Manufacturer NKK Switches Category Switches Package - Series S Circuit DPDT Switch Function Mom-Off-Mom Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features - Report errors?		
CategorySwitchesPackage-SeriesSCircuitDPDTSwitch FunctionMom-Off-MomCurrent Rating15A (AC), 20A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Manufacturer Part Number	S28AW
Package - Series S Circuit DPDT Switch Function Mom-Off-Mom Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features - Series Signature Signat	Manufacturer	NKK Switches
Package - Series S Circuit DPDT Switch Function Mom-Off-Mom Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Category	Switches
SeriesSCircuitDPDTSwitch FunctionMom-Off-MomCurrent Rating15A (AC), 20A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress ProtectionIP67 - Dust Tight, WaterproofFeatures-		Toggle Switches
CircuitDPDTSwitch FunctionMom-Off-MomCurrent Rating15A (AC), 20A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Package	-
Switch FunctionMom-Off-MomCurrent Rating15A (AC), 20A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Series	S
Current Rating 15A (AC), 20A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection Features 125V 30V 30V 30V Actuator Length Institute Round Non-Illumination Non-Illuminated Ingress Protection Ingress	Switch Function	Mom-Off-Mom
Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection Features - Standard Round Non-Illumination Non-Illuminated Non-Illuminated Non-Illuminated Voltage Circular - 12.50mm Dia Non-Illuminated Non-Illuminated Non-Illuminated Non-Illuminated Voltage Non-Illuminated Non-Illuminated Voltage Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Non-Illuminated Voltage Non-Illuminated Voltage Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Voltage (Noninal) Volt	Current Rating	15A (AC), 20A (DC)
Actuator Type Standard Round 17.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Voltage Rating - AC	125V
Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Voltage Rating - DC	30V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Actuator Length	17.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress ProtectionIP67 - Dust Tight, WaterproofFeatures-	Illumination Type, Color	-
Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Mounting Type	Panel Mount
Bushing Thread M12 x 1 Ingress Protection IP67 - Dust Tight, Waterproof Features -	Termination Style	Solder Lug
Ingress Protection IP67 - Dust Tight, Waterproof Features -	Panel Cutout Dimensions	Circular - 12.50mm Dia
Features -	Bushing Thread	M12 x 1
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	-
		Report errors?

S28AW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S28AW Payment Methods



















S28AW Shipping Methods













If you have any question about S28AW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com