

S2EB-L-24V Information



For Reference Only

Part Number S2EB-L-24V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PST 4A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S2EB-L-24V Specifications

Manufacturer Part Number S2EB-L-24V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series S Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.4mA Coil Voltage 24VDC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 4A Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesSRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.4mACoil Voltage24VDCContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)4ASwitching Voltage250VAC, 48VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - AmberMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	S2EB-L-24V
Package - Series S S Selay Type General Purpose Coil Type Latching, Single Coil Current 8.4mA Coil Voltage 24VDC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 4A Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style Purpose	Manufacturer	Panasonic Electric Works
Package-SeriesSRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.4mACoil Voltage24VDCContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)4ASwitching Voltage250VAC, 48VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - AmberMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesSRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.4mACoil Voltage24VDCContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)4ASwitching Voltage250VAC, 48VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - AmberMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.4mACoil Voltage24VDCContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)4ASwitching Voltage250VAC, 48VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - AmberMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Single Coil Coil Current 8.4mA Coil Voltage 24VDC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 4A Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Series	S
Coil Current 8.4mA Coil Voltage 24VDC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 4A Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 4A Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 4A Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Release Time Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Coil Current	8.4mA
Contact Rating (Current) Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style 4A 250VAC, 48VDC - Max 16.8 VDC	Coil Voltage	24VDC
Switching Voltage 250VAC, 48VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Contact Form	4PST (2 Form A, 2 Form B)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style 16.8 VDC	Contact Rating (Current)	4A
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 48VDC - Max
Operate Time 15ms Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 15ms Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Amber Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	15ms
Termination Style PC Pin	Features	Sealed - Amber
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

S2EB-L-24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S2EB-L-24V Payment Methods



















S2EB-L-24V Shipping Methods













If you have any question about S2EB-L-24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com