

S3-0R075J8

Request a Quote

S3-0R075J8 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



S3-0R075J8 Specifications

ManufacturerRiedonCategoryResistorsChip Resistor - Surface MountPackage6327 J-LeadSeriesSResistance75 mOhmsTolerance±5%Power (Watts)3WCompositionVirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyPoperature Coefficient-5°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Siz / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2			
CategoryResistorsChip Resistor - Surface MountPackage6327 J-LeadSeriesSResistance75 mOhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTolperature Coefficient-Operating Temperature55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626° L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2Failure Rate-	Manufacturer Part Number	S3-0R075J8	
Chip Resistor - Surface MountPackage6327 J-LeadSeriesSResistance75 mOhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyPoperating Temperature-Operating Temperature6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2Failure Rate-	Manufacturer	Riedon	
Package6327 J-LeadSeriesSResistance75 mOhmsTolerance±5%Power (Wats)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyPoperating Temperature-Operating Temperature55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Category	Resistors	
SeriesSSeriesSResistance75 mOhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient-Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount	
Resistance75 mOhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient-Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Package	6327 J-Lead	
Tolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient-Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626° L x 0.272° W (15.90mm x 6.90mm)Height - Seated (Max)0.268° (6.80mm)Number of Terminations2Failure Rate-	Series	S	
Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient-Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Resistance	75 mOhms	
CompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient-Operating Temperature-55°C ~ 275°COperating Temperature6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 5\%$	
FeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient-Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Power (Watts)	3W	
Temperature Coefficient-Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Composition	Wirewound	
Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Features	Flame Proof, Moisture Resistant, Pulse Withstanding, Safety	
Package / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Temperature Coefficient	-	
Supplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 275°C	
Size / Dimension 0.626" L x 0.272" W (15.90mm x 6.90mm) Height - Seated (Max) 0.268" (6.80mm) Number of Terminations 2 Failure Rate -	Package / Case	6327 J-Lead	
Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Supplier Device Package	-	
Number of Terminations 2 Failure Rate -	Size / Dimension	0.626" L x 0.272" W (15.90mm x 6.90mm)	
Failure Rate -	Height - Seated (Max)	0.268" (6.80mm)	
	Number of Terminations	2	
Report errors?	Failure Rate	-	
			Report errors?

S3-0R075J8 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

S3-0R075J8 Payment Methods



S3-0R075J8 Shipping Methods



If you have any question about S3-0R075J8, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com