

# S3-10RJ8

### S3-10RJ8 Information



Part Number	S3-10RJ8	
Manufacturer	Riedon	
Category	Resistors Chip Resistor - Surface Mount	
Description	RES SMD 10 OHM 5% 3W 6327	
Package	6327 J-Lead	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

# For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## S3-10RJ8 Specifications

Manufacturer Part Number S3-10RJ8   Manufacturer Riedon   Category Resistors   Chip Resistor - Surface Mount Chip Resistor - Surface Mount   Package 6327 J-Lead   Series S   Resistance 10 Ohms   Tolerance ±5%   Power (Watts) 3W   Composition Wirewound   Features Flame Proof, Moisture Resistant, Pulse Withstanding, Safety   Power (Qate) ±50°C   Operating Temperature 55°C ~ 275°C   Package / Case 6327 J-Lead   Supplier Device Package -   Size / Dimension 0.626° L x 0.272° W (15.90mm x 6.90mm)   Height - Seated (Max) 2   Number of Terminations 2   Failure Rate -		
CategoryResistorsChip Resistor - Surface MountPackage6327 J-LeadSeriesSResistance10 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyOperating Temperaturee55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package.Size / Dimension0.626° L x 0.272° W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate.	Manufacturer Part Number	S3-10RJ8
Chip Resistor - Surface MountPackage6327 J-LeadSeriesSResistance10 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626° L x 0.272° W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Manufacturer	Riedon
Package6327 J-LeadSeriesSResistance10 OhmsTolerance±5%Power (Wats)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyPoperating Temperature±50pm/°COperating Temperature6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Category	Resistors
SeriesSSeriesSResistance10 OhmsTolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount
Resistance10 OhmsTolerance $5\%$ Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient $50pm^{\circ}C$ Operating Temperature $55^{\circ}C \sim 275^{\circ}C$ Package / Case $6327$ J-LeadSupplier Device Package $-$ Size / Dimension $0.626^{\circ}L x 0.272^{\circ}W (15.90mm x 6.90mm)$ Height - Seated (Max) $2$ Number of Terminations $2$ Failure Rate $-$	Package	6327 J-Lead
Tolerance±5%Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Series	S
Power (Watts)3WCompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-0.626° L x 0.272° W (15.90mm x 6.90mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Resistance	10 Ohms
CompositionWirewoundFeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Tolerance	±5%
FeaturesFlame Proof, Moisture Resistant, Pulse Withstanding, SafetyTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Power (Watts)	3W
Temperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Composition	Wirewound
Operating Temperature-55°C ~ 275°CPackage / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Features	Flame Proof, Moisture Resistant, Pulse Withstanding, Safety
Package / Case6327 J-LeadSupplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±50ppm/°C
Supplier Device Package-Size / Dimension0.626" L x 0.272" W (15.90mm x 6.90mm)Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 275°C
Size / Dimension 0.626" L x 0.272" W (15.90mm x 6.90mm)   Height - Seated (Max) 0.268" (6.80mm)   Number of Terminations 2   Failure Rate -	Package / Case	6327 J-Lead
Height - Seated (Max)0.268" (6.80mm)Number of Terminations2Failure Rate-	Supplier Device Package	-
Number of Terminations2Failure Rate-	Size / Dimension	0.626" L x 0.272" W (15.90mm x 6.90mm)
Failure Rate -	Height - Seated (Max)	0.268" (6.80mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

### S3-10RJ8 Guarantees



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about S3-10RJ8, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com