



S4006DS2TP Information



For Reference Only

Part Number S4006DS2TP **Manufacturer** Littelfuse Inc.

Category Discrete Semiconductor Products

Thyristors - SCRs

Description SCR SENS 400V 6A TO-252

Package TO-252-3, DPak (2 Leads + Tab), SC-63

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S4006DS2TP Specifications

Manufacturer \$4006D82TP Manufacturer Littelfuse Inc. Category Discrete Semiconductor Products Thyristors - SCRs Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Voltage - Off State 400V Voltage - Gate Trigger (Vgt) (Max) 800mV Current - Gate Trigger (Igt) (Max) 200μA Voltage - On State (Vtm) (Max) 1.6V Current - On State (It (AV)) (Max) 3.8A Current - On State (It (RMS)) (Max) 6A Current - Hold (Ih) (Max) 6mA Current - Off State (Max) 5μA Current - Non Rep. Surge 50, 60Hz (Itsm) 83A, 100A SCR Type Sensitive Gate Operating Temperature -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TO-252, (D-Pak)		
CategoryDiscrete Semiconductor ProductsPackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Voltage - Off State400VVoltage - Gate Trigger (Vgt) (Max)800mVCurrent - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.6VCurrent - On State (It (AV)) (Max)3.8ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)6mACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeSensitive GateOperating Temperature-40°C ~ 110°CMounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTO-252, (D-Pak)	Manufacturer Part Number	S4006DS2TP
Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Voltage - Off State 400V Voltage - Gate Trigger (Vgt) (Max) 800mV Current - Gate Trigger (Igt) (Max) 200μA Voltage - On State (Vtm) (Max) 1.6V Current - On State (It (AV)) (Max) 3.8A Current - On State (It (RMS)) (Max) 6A Current - Hold (Ih) (Max) 6mA Current - Off State (Max) 5μA Current - Non Rep. Surge 50, 60Hz (Itsm) 83A, 100A SCR Type Sensitive Gate Operating Temperature -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TO-252, (D-Pak)	Manufacturer	Littelfuse Inc.
PackageTO-252-3, DPak (2 Leads + Tab), SC-63Series-Voltage - Off State400VVoltage - Gate Trigger (Vgt) (Max)800mVCurrent - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.6VCurrent - On State (It (AV)) (Max)3.8ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)6mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeSensitive GateOperating Temperature-40°C ~ 110°CMounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTO-252, (D-Pak)	Category	Discrete Semiconductor Products
Series-Voltage - Off State400 VVoltage - Gate Trigger (Vgt) (Max)800 mVCurrent - Gate Trigger (Igt) (Max)200 μAVoltage - On State (Vtm) (Max)1.6 VCurrent - On State (It (AV)) (Max)3.8 ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)6mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeSensitive GateOperating Temperature-40°C ~ 110°CMounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTO-252, (D-Pak)		Thyristors - SCRs
Voltage - Off State Voltage - Gate Trigger (Vgt) (Max) Current - Gate Trigger (Igt) (Max) Voltage - On State (Vtm) (Max) Current - On State (It (AV)) (Max) Current - On State (It (RMS)) (Max) Current - Hold (Ih) (Max) Current - Off State (Max) Current - Off State (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) SCR Type Sensitive Gate Operating Temperature -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TO-252, (D-Pak)	Package	TO-252-3, DPak (2 Leads + Tab), SC-63
Voltage - Gate Trigger (Vgt) (Max)800mVCurrent - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.6VCurrent - On State (It (AV)) (Max)3.8ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)6mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeSensitive GateOperating Temperature-40°C ~ 110°CMounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTO-252, (D-Pak)	Series	-
Current - Gate Trigger (Igt) (Max)200μAVoltage - On State (Vtm) (Max)1.6VCurrent - On State (It (AV)) (Max)3.8ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)6mACurrent - Off State (Max)5μACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeSensitive GateOperating Temperature-40°C ~ 110°CMounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTO-252, (D-Pak)	Voltage - Off State	400V
Voltage - On State (Vtm) (Max) Current - On State (It (AV)) (Max) 3.8A Current - On State (It (RMS)) (Max) 6A Current - Hold (Ih) (Max) Current - Off State (Max) 5µA Current - Non Rep. Surge 50, 60Hz (Itsm) 83A, 100A SCR Type Sensitive Gate Operating Temperature -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package	Voltage - Gate Trigger (Vgt) (Max)	800mV
Current - On State (It (AV)) (Max) Current - On State (It (RMS)) (Max) 6A Current - Hold (Ih) (Max) 6mA Current - Off State (Max) Current - Non Rep. Surge 50, 60Hz (Itsm) 83A, 100A SCR Type Sensitive Gate Operating Temperature -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package	Current - Gate Trigger (Igt) (Max)	200μΑ
Current - On State (It (RMS)) (Max) Current - Hold (Ih) (Max) 6mA Current - Off State (Max) 5μA Current - Non Rep. Surge 50, 60Hz (Itsm) 83A, 100A SCR Type Sensitive Gate Operating Temperature -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package	Voltage - On State (Vtm) (Max)	1.6V
Current - Hold (Ih) (Max) $6mA$ Current - Off State (Max) $5\mu A$ Current - Non Rep. Surge 50, 60Hz (Itsm) $83A$, $100A$ SCR TypeSensitive GateOperating Temperature $-40^{\circ}\text{C} \sim 110^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $TO-252-3$, $DPak$ (2 Leads + Tab), SC-63Supplier Device Package $TO-252$, $(D-Pak)$	Current - On State (It (AV)) (Max)	3.8A
Current - Off State (Max) $5\mu A$ Current - Non Rep. Surge 50, 60Hz (Itsm) $83A$, $100A$ SCR Type Sensitive Gate Operating Temperature $-40^{\circ}C \sim 110^{\circ}C$ Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package	Current - On State (It (RMS)) (Max)	6A
Current - Non Rep. Surge 50, 60Hz (Itsm) 83A, 100A SCR Type Sensitive Gate -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TO-252, (D-Pak)	Current - Hold (Ih) (Max)	6mA
SCR TypeSensitive GateOperating Temperature-40°C ~ 110°CMounting TypeSurface MountPackage / CaseTO-252-3, DPak (2 Leads + Tab), SC-63Supplier Device PackageTO-252, (D-Pak)	Current - Off State (Max)	5μΑ
Operating Temperature -40°C ~ 110°C Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TO-252, (D-Pak)	Current - Non Rep. Surge 50, 60Hz (Itsm)	83A, 100A
Mounting Type Surface Mount Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TO-252, (D-Pak)	SCR Type	Sensitive Gate
Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63 Supplier Device Package TO-252, (D-Pak)	Operating Temperature	-40°C ~ 110°C
Supplier Device Package TO-252, (D-Pak)	Mounting Type	Surface Mount
	Package / Case	TO-252-3, DPak (2 Leads + Tab), SC-63
Report errors?	Supplier Device Package	TO-252, (D-Pak)
		Report errors?

S4006DS2TP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S4006DS2TP Payment Methods



















S4006DS2TP Shipping Methods













If you have any question about S4006DS2TP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com