

### **S422 Information**



For Reference Only

Part Number S422

Manufacturer NKK Switches
Category Switches

Toggle Switches

**Description** SWITCH TOGGLE DPDT 25A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **S422 Specifications**

| Manufacturer Part Number         \$422           Manufacturer         NKK Switches           Category         Switches           Package         -           Series         \$400           Circuit         DPDT           Switch Function         On-On           Current Rating         \$25 A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         -  |                                |                        |
|--|--------------------------------|------------------------|
| Category         Switches           Package         -           Series         \$400           Circuit         DPDT           Switch Function         On-On           Current Rating         25A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         -  | Manufacturer Part Number       | S422                   |
| Package - Series S400 Circuit DPDT Switch Function On-On Current Rating 25A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Standard Round Actuator Type Standard Round 17.50mm Illumination Type, Color 11umination Type, Color - Illumination Type, Color 11umination Voltage (Nominal) - Monting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features - Series Solder Lug Features - Series Solder Sol | Manufacturer                   | NKK Switches           |
| Package         -           Series         \$400           Circuit         DPDT           Switch Function         On-On           Current Rating         25A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         -  | Category                       | Switches               |
| Series         \$400           Circuit         DPDT           Switch Function         On-On           Current Rating         25A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         -  |                                | Toggle Switches        |
| CircuitDPDTSwitch FunctionOn-OnCurrent Rating25A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-  | Package                        | -                      |
| Switch Function On-On Current Rating 25A (AC) Voltage Rating - AC 125V  Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection Features   | Series                         | S400                   |
| Current Rating 25A (AC)  Voltage Rating - AC 125V  Voltage Rating - DC Standard Round  Actuator Type Standard Round  Actuator Length 17.50mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) - Solder Lug  Panel Mount Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection - Features   | Circuit                        | DPDT                   |
| Voltage Rating - AC  Voltage Rating - DC  Actuator Type  Standard Round  Actuator Length  17.50mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Panel Cutout Dimensions  Bushing Thread  Ingress Protection  Features  125V  -  Standard Round  -  Panel Mound  17.50mm  Non-Illuminated  17.50mm  Non-Illuminated  Non-Illuminated  17.50mm  Non-Illuminated  Ingress Protection  -  -  -  -  -  -  -  -  -  -  -  -  -  | Switch Function                | On-On                  |
| Voltage Rating - DC-Actuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-  | Current Rating                 | 25A (AC)               |
| Actuator Type Standard Round Actuator Length 17.50mm  Illumination Non-Illuminated  Illumination Type, Color Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection -  Features -  Standard Round  17.50mm  Standard Round  17.50mm  Non-Illuminated  -  Solder Lug  Solder Lug  All 2 x 1  Ingress Protection  -  Features -  Standard Round  17.50mm  Non-Illuminated  -  -  -  -  -  -  -  -  -  -  -  -  -  | Voltage Rating - AC            | 125V                   |
| Actuator Length 17.50mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection -  Features -  Features -  17.50mm  Circular -  Circul | Voltage Rating - DC            | -                      |
| Illumination Non-Illuminated  Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection Features   | Actuator Type                  | Standard Round         |
| Illumination Type, Color Illumination Voltage (Nominal)  Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -  | Actuator Length                | 17.50mm                |
| Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection - Features -   | Illumination                   | Non-Illuminated        |
| Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-  | Illumination Type, Color       | -                      |
| Termination Style  Panel Cutout Dimensions  Circular - 12.50mm Dia  Bushing Thread  M12 x 1  Ingress Protection  Features  | Illumination Voltage (Nominal) | -                      |
| Panel Cutout Dimensions  Bushing Thread  M12 x 1  Ingress Protection  Features  Circular - 12.50mm Dia  M12 x 1  | Mounting Type                  | Panel Mount            |
| Bushing Thread M12 x 1 Ingress Protection Features   | Termination Style              | Solder Lug             |
| Ingress Protection - Features -  | Panel Cutout Dimensions        | Circular - 12.50mm Dia |
| Features -   | Bushing Thread                 | M12 x 1                |
|  | Ingress Protection             | -                      |
| Report errors?   | Features                       | -                      |
|  |                                | Report errors?         |

#### **S422 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **S422 Payment Methods**



















## **S422 Shipping Methods**













If you have any question about S422, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com