

**S4B-ZR-SM3A-TF Information**


For Reference Only

**Part Number** [S4B-ZR-SM3A-TF](#)  
**Manufacturer** JST Sales America Inc.  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN HEADER ZH SIDE 4POS 1.5MM  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**S4B-ZR-SM3A-TF Specifications**

|                            |  |
|----------------------------|--|
| Manufacturer Part Number   | <a href="#">S4B-ZR-SM3A-TF</a>   |
| Manufacturer               | JST Sales America Inc.   |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -  |
| Series                     | ZH   |
| Connector Type             | Header   |
| Contact Type               | Male Pin   |
| Pitch - Mating             | 0.059" (1.50mm)  |
| Style                      | Board to Cable/Wire  |
| Shrouding                  | Shrouded - 4 Wall  |
| Number of Positions        | 4  |
| Number of Positions Loaded | All  |
| Number of Rows             | 1  |
| Row Spacing - Mating       | -  |
| Mounting Type              | Surface Mount, Right Angle   |
| Termination                | Solder   |
| Fastening Type             | Detent Lock  |
| Contact Length - Mating    | -  |
| Contact Length - Post      | -  |
| Overall Contact Length     | -  |
| Insulation Height          | 0.146" (3.71mm)  |
| Contact Shape              | Circular   |
| Contact Finish - Mating    | Tin-Lead   |

|                                   |   |
|-----------------------------------|---|
| Contact Finish Thickness - Mating | -   |
| Contact Finish - Post             | Tin-Lead                                  |
| Contact Material                  | Brass                                     |
| Insulation Material               | Polyamide (PA46), Nylon 4/6, Glass Filled |
| Features                          | Solder Retention                          |
| Operating Temperature             | -25°C ~ 85°C                              |
| Ingress Protection                | -   |
| Material Flammability Rating      | UL94 V-0                                  |
| Insulation Color                  | Natural                                   |
|                                   | <a href="#">Report errors?</a>            |

### S4B-ZR-SM3A-TF Guarantees



#### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### S4B-ZR-SM3A-TF Payment Methods



### S4B-ZR-SM3A-TF Shipping Methods



If you have any question about S4B-ZR-SM3A-TF, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)