



### **S6006VTP Information**



For Reference Only

**Part Number** S6006VTP **Manufacturer** Littelfuse Inc.

Category Discrete Semiconductor Products

Thyristors - SCRs

**Description**SCR NON-SENS 600V 6A TO-251**Package**TO-251-3 Short Leads, IPak, TO-251AA

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **S6006VTP Specifications**

Manufacturer Part Number         \$6006VTP           Manufacturer         Littelfuse Inc.           Category         Discrete Semiconductor Products           Thyristors - SCRs           Package         TO-251-3 Short Leads, IPak, TO-251AA           Series         -           Voltage - Off State         600V           Voltage - Gate Trigger (Vgt) (Max)         1.5V           Current - Gate Trigger (Igt) (Max)         15mA           Voltage - On State (Vtm) (Max)         1.6V           Current - On State (It (AV)) (Max)         3.8A           Current - On State (It (RMS)) (Max)         6A           Current - Hold (Ih) (Max)         30mA           Current - Off State (Max)         10µA           Current - Non Rep. Surge 50, 60Hz (Itsm)         83A, 100A           SCR Type         Standard Recovery           Operating Temperature         -40°C ~ 125°C           Mounting Type         Through Hole           Package / Case         TO-251-3 Short Leads, IPak, TO-251AA           Supplier Device Package         TO-251 (V-Pak/I-Pak)		
CategoryDiscrete Semiconductor ProductsThyristors - SCRsPackageTO-251-3 Short Leads, IPak, TO-251AASeries-Voltage - Off State600VVoltage - Gate Trigger (Vgt) (Max)1.5VCurrent - Gate Trigger (Igt) (Max)15mAVoltage - On State (Vtm) (Max)1.6VCurrent - On State (It (AV)) (Max)3.8ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)30mACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeStandard RecoveryOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-251-3 Short Leads, IPak, TO-251AASupplier Device PackageTO-251 (V-Pak/I-Pak)	Manufacturer Part Number	S6006VTP
Package         TO-251-3 Short Leads, IPak, TO-251AA           Series         -           Voltage - Off State         600V           Voltage - Gate Trigger (Vgt) (Max)         1.5V           Current - Gate Trigger (Igt) (Max)         15mA           Voltage - On State (Vtm) (Max)         1.6V           Current - On State (It (AV)) (Max)         3.8A           Current - On State (It (RMS)) (Max)         6A           Current - Hold (Ih) (Max)         30mA           Current - Off State (Max)         10μA           Current - Non Rep. Surge 50, 60Hz (Itsm)         83A, 100A           SCR Type         Standard Recovery           Operating Temperature         -40°C ~ 125°C           Mounting Type         Through Hole           Package / Case         TO-251-3 Short Leads, IPak, TO-251AA           Supplier Device Package         TO-251 (V-Pak/I-Pak)	Manufacturer	Littelfuse Inc.
PackageTO-251-3 Short Leads, IPak, TO-251AASeries-Voltage - Off State600VVoltage - Gate Trigger (Vgt) (Max)1.5VCurrent - Gate Trigger (Igt) (Max)15mAVoltage - On State (Vtm) (Max)1.6VCurrent - On State (It (AV)) (Max)3.8ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)30mACurrent - Off State (Max)10μACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeStandard RecoveryOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-251-3 Short Leads, IPak, TO-251AASupplier Device PackageTO-251 (V-Pak/I-Pak)	Category	Discrete Semiconductor Products
Series         -           Voltage - Off State         600 V           Voltage - Gate Trigger (Vgt) (Max)         1.5 V           Current - Gate Trigger (Igt) (Max)         15mA           Voltage - On State (Vtm) (Max)         1.6 V           Current - On State (It (AV)) (Max)         3.8A           Current - On State (It (RMS)) (Max)         6A           Current - Hold (Ih) (Max)         30mA           Current - Off State (Max)         10μA           Current - Non Rep. Surge 50, 60Hz (Itsm)         83A, 100A           SCR Type         Standard Recovery           Operating Temperature         -40°C ~ 125°C           Mounting Type         Through Hole           Package / Case         TO-251-3 Short Leads, IPak, TO-251AA           Supplier Device Package         TO-251 (V-Pak/I-Pak)		Thyristors - SCRs
Voltage - Off State  Voltage - Gate Trigger (Vgt) (Max)  1.5V  Current - Gate Trigger (Igt) (Max)  Voltage - On State (Vtm) (Max)  1.6V  Current - On State (It (AV)) (Max)  3.8A  Current - On State (It (RMS)) (Max)  6A  Current - Hold (Ih) (Max)  Current - Off State (Max)  Current - Off State (Max)  Current - Non Rep. Surge 50, 60Hz (Itsm)  SCR Type  Standard Recovery  Operating Temperature  -40°C ~ 125°C  Mounting Type  Through Hole  Package / Case  TO-251-3 Short Leads, IPak, TO-251AA  Supplier Device Package  TO-251 (V-Pak/I-Pak)	Package	TO-251-3 Short Leads, IPak, TO-251AA
Voltage - Gate Trigger (Vgt) (Max)  Current - Gate Trigger (Igt) (Max)  15mA  Voltage - On State (Vtm) (Max)  1.6V  Current - On State (It (AV)) (Max)  3.8A  Current - On State (It (RMS)) (Max)  6A  Current - Hold (Ih) (Max)  30mA  Current - Off State (Max)  10µA  Current - Non Rep. Surge 50, 60Hz (Itsm)  83A, 100A  SCR Type  Standard Recovery  Operating Temperature  40°C ~ 125°C  Mounting Type  Through Hole  Package / Case  TO-251-3 Short Leads, IPak, TO-251AA  Supplier Device Package  TO-251 (V-Pak/I-Pak)	Series	-
Current - Gate Trigger (Igt) (Max)15mAVoltage - On State (Vtm) (Max)1.6VCurrent - On State (It (AV)) (Max)3.8ACurrent - On State (It (RMS)) (Max)6ACurrent - Hold (Ih) (Max)30mACurrent - Off State (Max)10μACurrent - Non Rep. Surge 50, 60Hz (Itsm)83A, 100ASCR TypeStandard RecoveryOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-251-3 Short Leads, IPak, TO-251AASupplier Device PackageTO-251 (V-Pak/I-Pak)	Voltage - Off State	600V
Voltage - On State (Vtm) (Max)  Current - On State (It (AV)) (Max)  3.8A  Current - On State (It (RMS)) (Max)  6A  Current - Hold (Ih) (Max)  Current - Off State (Max)  10μA  Current - Non Rep. Surge 50, 60Hz (Itsm)  83A, 100A  SCR Type  Standard Recovery  Operating Temperature  -40°C ~ 125°C  Mounting Type  Through Hole  Package / Case  TO-251-3 Short Leads, IPak, TO-251AA  Supplier Device Package  TO-251 (V-Pak/I-Pak)	Voltage - Gate Trigger (Vgt) (Max)	1.5V
Current - On State (It (AV)) (Max)  Current - On State (It (RMS)) (Max)  6A  Current - Hold (Ih) (Max)  Current - Off State (Max)  Current - Non Rep. Surge 50, 60Hz (Itsm)  SCR Type  Standard Recovery  Operating Temperature  -40°C ~ 125°C  Mounting Type  Through Hole  Package / Case  TO-251-3 Short Leads, IPak, TO-251AA  Supplier Device Package	Current - Gate Trigger (Igt) (Max)	15mA
Current - On State (It (RMS)) (Max)  Current - Hold (Ih) (Max)  30mA  Current - Off State (Max)  10μA  Current - Non Rep. Surge 50, 60Hz (Itsm)  83A, 100A  SCR Type  Standard Recovery  Operating Temperature  -40°C ~ 125°C  Mounting Type  Through Hole  Package / Case  TO-251-3 Short Leads, IPak, TO-251AA  Supplier Device Package	Voltage - On State (Vtm) (Max)	1.6V
Current - Hold (Ih) (Max) 30mA   Current - Off State (Max) 10 $\mu$ A   Current - Non Rep. Surge 50, 60Hz (Itsm) 83A, 100A   SCR Type Standard Recovery   Operating Temperature -40°C ~ 125°C   Mounting Type Through Hole   Package / Case TO-251-3 Short Leads, IPak, TO-251AA   Supplier Device Package TO-251 (V-Pak/I-Pak)	Current - On State (It (AV)) (Max)	3.8A
Current - Off State (Max) $10\mu A$ Current - Non Rep. Surge 50, 60Hz (Itsm) $83A, 100A$ SCR Type $Standard Recovery$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type $Through Hole$ Package / Case $TO-251-3 Short Leads, IPak, TO-251AA$ Supplier Device Package $TO-251 (V-Pak/I-Pak)$	Current - On State (It (RMS)) (Max)	6A
Current - Non Rep. Surge 50, 60Hz (Itsm)  83A, 100A  SCR Type  Standard Recovery  -40°C ~ 125°C  Mounting Type  Through Hole  Package / Case  TO-251-3 Short Leads, IPak, TO-251AA  Supplier Device Package  TO-251 (V-Pak/I-Pak)	Current - Hold (Ih) (Max)	30mA
SCR TypeStandard RecoveryOperating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseTO-251-3 Short Leads, IPak, TO-251AASupplier Device PackageTO-251 (V-Pak/I-Pak)	Current - Off State (Max)	10μΑ
Operating Temperature  -40°C ~ 125°C  Mounting Type  Through Hole  Package / Case  TO-251-3 Short Leads, IPak, TO-251AA  Supplier Device Package  TO-251 (V-Pak/I-Pak)	Current - Non Rep. Surge 50, 60Hz (Itsm)	83A, 100A
Mounting Type Through Hole Package / Case TO-251-3 Short Leads, IPak, TO-251AA Supplier Device Package TO-251 (V-Pak/I-Pak)	SCR Type	Standard Recovery
Package / Case TO-251-3 Short Leads, IPak, TO-251AA Supplier Device Package TO-251 (V-Pak/I-Pak)	Operating Temperature	-40°C ~ 125°C
Supplier Device Package TO-251 (V-Pak/I-Pak)	Mounting Type	Through Hole
	Package / Case	TO-251-3 Short Leads, IPak, TO-251AA
Report errors?	Supplier Device Package	TO-251 (V-Pak/I-Pak)
		Report errors?

#### **S6006VTP Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **S6006VTP Payment Methods**


































If you have any question about S6006VTP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com