

S8-0504 Information

www.heisener.com

For Reference Only

Part Number S8-0504
Manufacturer Cynergy 3
Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 1A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S8-0504 Specifications

Manufacturer Part Number\$8-0504ManufacturerCynergy 3CategoryRelaysPackage-Series\$8Relay TypeReedCoil TypeNon LatchingCoil Current41.7mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)1ASwitching Voltage300VAC, 350VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)1 VDCOperate TimeImsRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
Category Relays Signal Relays, Up to 2 Amps Package - Series S8 Relay Type Reed Coil Type Non Latching Coil Current 41.7mA Coil Voltage SYDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 1 VDC Operate Time Ims Release Time 0.5ms Features Mounting Type Trong Hole	Manufacturer Part Number	S8-0504
Package - Series S8 Relay Type Reed Coil Type Non Latching Coil Current 41.7mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Trhrough Hole	Manufacturer	Cynergy 3
Package - Series S8 Relay Type Reed Coil Type Non Latching Coil Current 41.7mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1ms Release Time 0.5ms Features - Through Hole	Category	Relays
SeriesS8Relay TypeReedCoil TypeNon LatchingCoil Current41.7mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)1ASwitching Voltage300VAC, 350VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)1 VDCOperate Time1msRelease Time0.5msFeatures-Mounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay Type Reed Coil Type Non Latching Coil Current 41.7mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1 Ims Release Time 0.5ms Features - Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 41.7mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole	Series	S8
Coil Current 41.7mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole	Relay Type	Reed
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 1A Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time Ims Release Time 0.5ms Features Mounting Type Through Hole	Coil Current	41.7mA
Contact Rating (Current) Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1ms Release Time 0.5ms Features Mounting Type Through Hole	Coil Voltage	5VDC
Switching Voltage 300VAC, 350VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 1 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Ims Release Time 0.5ms Features Mounting Type Through Hole	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time Ims Release Time 0.5ms Features Mounting Type Through Hole	Switching Voltage	300VAC, 350VDC - Max
Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	4 VDC
Release Time 0.5ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	1 VDC
Features - Mounting Type Through Hole	Operate Time	1ms
Mounting Type Through Hole	Release Time	0.5ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

S8-0504 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S8-0504 Payment Methods



















S8-0504 Shipping Methods













If you have any question about S8-0504, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com