

S822/CUL Information



For Reference Only

Part Number S822/CUL
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 30A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S822/CUL Specifications

Manufacturer Part Number S822/CUL Manufacturer NKK Switches Category Switches Package - Series S Circuit DPDT Switch Function On-On Current Rating 30A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 22.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features - Features -		
Category Switches Package - Series S Circuit DPDT Switch Function On-On Current Rating 30A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 22.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Manufacturer Part Number	S822/CUL
Package - Series S Circuit DPDT Switch Function On-On Current Rating 30A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round 22.00mm Illumination Type, Color 12luminated 11lumination Type, Color 11lumination Type, Color 11lumination Type Panel Mount 72pe Panel	Manufacturer	NKK Switches
Package - Series S Circuit DPDT Switch Function On-On Current Rating 30A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 22.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Category	Switches
Series S Circuit DPDT Switch Function On-On Current Rating 30A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 22.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating30A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length22.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Package	-
Switch FunctionOn-OnCurrent Rating30A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length22.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Series	S
Current Rating30A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length22.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Circuit	DPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length22.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Switch Function	On-On
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length22.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Current Rating	30A (AC/DC)
Actuator TypeStandard RoundActuator Length22.00mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Voltage Rating - AC	125V
Actuator Length 22.00mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Screw Termination Style Screw Terminal Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Actuator Length	22.00mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleScrew TerminalPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-Features-	Illumination Type, Color	-
Termination Style Screw Terminal Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread M12 x 1 Ingress Protection Features Circular - 12.50mm Dia M12 x 1 -	Mounting Type	Panel Mount
Bushing Thread M12 x 1 Ingress Protection - Features -	Termination Style	Screw Terminal
Ingress Protection - Features -	Panel Cutout Dimensions	Circular - 12.50mm Dia
Features -	Bushing Thread	M12 x 1
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

S822/CUL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S822/CUL Payment Methods



















S822/CUL Shipping Methods













If you have any question about S822/CUL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com