

### S82K-03024 Information



For Reference Only

Part Number S82K-03024

Manufacturer Omron Automation and Safety

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 24V 30W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









COM	<b>0202</b> 4	Specifica	tiona
304N	·UJUZ4	Specifica	uons

Manufacturer Part Number         S82K-03024           Manufacturer         Omron Automation and Safety           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         S82K           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.3A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         66%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         DIN Rail           Size / Dimension         3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         S82K           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.3A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         66%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         DIN Rail           Size / Dimension         3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Manufacturer Part Number	S82K-03024	
Package         -           Series         S82K           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.3A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         66%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         DIN Rail           Size / Dimension         3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Manufacturer	Omron Automation and Safety	
Package         -           Series         \$82K           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.3A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         66%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         DIN Rail           Size / Dimension         3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         S82K           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.3A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         66%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         DIN Rail           Size / Dimension         3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)		AC DC Converters	
Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         1.3A           Power (Watts)         30W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         66%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         DIN Rail           Size / Dimension         3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Package	-	
Number of Outputs       1         Voltage - Input       100 ~ 240 VAC         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       1.3A         Power (Watts)       30W         Applications       ITE (Commercial)         Voltage - Isolation       3kV (3000V)         Efficiency       66%         Operating Temperature       -10°C ~ 60°C (With Derating)         Features       Adjustable Output, Remote Sense, Universal Input         Mounting Type       DIN Rail         Size / Dimension       3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Series	S82K	
Voltage - Input100 ~ 240 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)1.3APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency66%Operating Temperature-10°C ~ 60°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeDIN RailSize / Dimension3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Туре	Enclosed	
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Site of oo'C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type DIN Rail Size / Dimension  24V  24V  24V  24V  24V  24V  24V  24	Number of Outputs	1	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  SkV (3000V)  Efficiency  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  DIN Rail  Size / Dimension	Voltage - Input	100 ~ 240 VAC	
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  66%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  DIN Rail  Size / Dimension  3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Voltage - Output 1	24V	
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  66%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  DIN Rail  Size / Dimension  3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Voltage - Output 2	-	
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  66%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  DIN Rail  Size / Dimension  1.3A  1.3A  30W  ITE (Commercial)  3kV (3000V)  66%  Commercial)  10°C ~ 60°C (With Derating)	Voltage - Output 3	-	
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  66%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  DIN Rail  Size / Dimension  3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Voltage - Output 4	-	
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	1.3A	
Voltage - Isolation 3kV (3000V)  Efficiency 66%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, Remote Sense, Universal Input  Mounting Type DIN Rail  Size / Dimension 3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Power (Watts)	30W	
Efficiency 66%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, Remote Sense, Universal Input  Mounting Type DIN Rail  Size / Dimension 3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Applications	ITE (Commercial)	
Operating Temperature -10°C ~ 60°C (With Derating)  Adjustable Output, Remote Sense, Universal Input  Mounting Type DIN Rail  Size / Dimension  3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Voltage - Isolation	3kV (3000V)	
Features Adjustable Output, Remote Sense, Universal Input  Mounting Type DIN Rail  Size / Dimension 3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Efficiency	66%	
Mounting Type DIN Rail Size / Dimension 3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Operating Temperature	-10°C ~ 60°C (With Derating)	
Size / Dimension 3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	Features	Adjustable Output, Remote Sense, Universal Input	
	Mounting Type	DIN Rail	
Report errors?	Size / Dimension	3.58" L x 3.54" W x 2.95" H (91.0mm x 90.0mm x 75.0mm)	
		Report errors?	

### S82K-03024 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## S82K-03024 Payment Methods



















### S82K-03024 Shipping Methods













If you have any question about S82K-03024, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com