



S86R11A1B1D1240 Information



For Reference Only

Part Number \$86R11A1B1D1240

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 20A 240V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S86R11A1B1D1240 Specifications

Manufacturer Part Number\$86R11A1B1D1240ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-Series\$86RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.5mACoil Voltage240VACContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)		
Category Relays Power Relays, Over 2 Amps Package - Series S86R Relay Type General Purpose Coil Type Non Latching Coil Current 16.5mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	S86R11A1B1D1240
Package - Series S86R Relay Type General Purpose Coil Type Non Latching Coil Current 16.5mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series S86R Relay Type General Purpose Coil Type Non Latching Coil Current 16.5mA Coil Voltage 240V AC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277V AC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Category	Relays
Series S86R Relay Type General Purpose Coil Type Non Latching Coil Current 16.5mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 16.5mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Non Latching Coil Current 16.5mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Series	S86R
Coil Current Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style 16.5mA	Relay Type	General Purpose
Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style DPDT (2 Form C) 20A 20A 277VAC - Max 204 VAC - Insulation - Class B Quick Connect - 0.250" (6.3mm)	Coil Current	16.5mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style 20A 277VAC - Max 204 VAC - 100 100 100 100 100 100 100	Coil Voltage	240VAC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style Cuick Connect - 0.250" (6.3mm)	Switching Voltage	277VAC - Max
Operate Time	Turn On Voltage (Max)	204 VAC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

S86R11A1B1D1240 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S86R11A1B1D1240 Payment Methods



















S86R11A1B1D1240 Shipping Methods













If you have any question about S86R11A1B1D1240, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com