



S87R11D2B1D1-24 Information



For Reference Only

Part Number S87R11D2B1D1-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 20A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S87R11D2B1D1-24 Specifications

Manufacturer Part Number S87R11D2B1D1-24 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 188mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm) Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 188mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	S87R11D2B1D1-24
Package - Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 188mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 188mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Category	Relays
Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 188mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 188mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Non Latching Coil Current 188mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Series	S87R
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time Release Time - Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style DPDT (2 Form C) 20A 277VAC - Max 18 VDC - Insulation - Class B Quick Connect - 0.250" (6.3mm)	Coil Current	188mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style 20A 277VAC - Max 277VAC - Max 18 VDC - 18 VDC - 18 VDC - Chassis Mount Chassis Mount Quick Connect - 0.250" (6.3mm)	Coil Voltage	24VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Switching Voltage	277VAC - Max
Operate Time	Turn On Voltage (Max)	18 VDC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
·	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

S87R11D2B1D1-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S87R11D2B1D1-24 Payment Methods





















S87R11D2B1D1-24 Shipping Methods













If you have any question about S87R11D2B1D1-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com