



#### S87R5D2B1D1-24 Information



For Reference Only

Part Number S87R5D2B1D1-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 20A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# S87R5D2B1D1-24 Specifications

Manufacturer Part Number  Manufacturer  TE Connectivity Potter & Brumfield Relays  Category  Relays  Power Relays, Over 2 Amps  Package  - Series  S87R  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  120mA  Coil Voltage  24VDC  Contact Form  SPDT (1 Form C)  Contact Rating (Current)  Correctivity Potter & Brumfield Relays  Brumfield Relays  Brumfield Relays  Formation of the serious properties of the serious p
Category Relays Power Relays, Over 2 Amps  Package - Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 120mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A
Package - Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 120mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A
Package - Series S87R Relay Type General Purpose Coil Type Non Latching Coil Current 120mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A
SeriesS87RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current120mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)20A
Relay Type General Purpose  Coil Type Non Latching  Coil Current 120mA  Coil Voltage 24VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 20A
Coil Type Non Latching  Coil Current 120mA  Coil Voltage 24VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 20A
Coil Current 120mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 20A
Contact Form SPDT (1 Form C) Contact Rating (Current) 20A
Contact Rating (Current) 20A
G : 1: W I
Switching Voltage 277VAC - Max
Turn On Voltage (Max) 18 VDC
Turn Off Voltage (Min) -
Operate Time -
Release Time -
Features Insulation - Class B
Mounting Type Chassis Mount
Termination Style Quick Connect - 0.250" (6.3mm)
Report errors?

#### S87R5D2B1D1-24 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## S87R5D2B1D1-24 Payment Methods



















## S87R5D2B1D1-24 Shipping Methods













If you have any question about S87R5D2B1D1-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com