

S8800B Information

Heisener.com

Part Number S8800B

Manufacturer Laird Technologies IAS

Category RF/IF and RFID

RF Antennas

Description ANTENNA 880-960NHZ 2DBI N FML

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S8800B Specifications

Manufacturer Part Number \$8800B Manufacturer Laird Technologies IAS Category RF/IF and RFID RF Antennas RF Antennas Package - Series - Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 920MHz Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm) Annlications WiMax?	*	
Category RF/IF and RFIID RF Antennas RF Antennas Package - Series - Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 920MHz Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Manufacturer Part Number	S8800B
Package - Series - Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 920MHz Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Manufacturer	Laird Technologies IAS
Package - Series - Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 920MHz Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Category	RF/IF and RFID
Series - Frequency Group UHF (300 MHz ~ 1 GHz) Frequency (Center/Band) 920MHz Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)		RF Antennas
Frequency Group Frequency (Center/Band) Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max Features - Termination Cable (432mm) - N Female Ingress Protection Mounting Type Bracket Mount Height (Max) UHF (300 MHz ~ 1 GHz) 920MHz 1041 105	Package	-
Frequency (Center/Band) 920MHz Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Series	-
Frequency Range 880MHz ~ 960MHz Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Frequency Group	UHF (300 MHz ~ 1 GHz)
Antenna Type Whip, Straight Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Frequency (Center/Band)	920MHz
Number of Bands 1 VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Frequency Range	880MHz ~ 960MHz
VSWR 1.5 Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Antenna Type	Whip, Straight
Return Loss - Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Number of Bands	1
Gain 2dBi Power - Max 5W Features - Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	VSWR	1.5
Power - Max 5W Features - Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Return Loss	-
Features - Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Gain	2dBi
Termination Cable (432mm) - N Female Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Power - Max	5W
Ingress Protection - Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Features	-
Mounting Type Bracket Mount Height (Max) 17.500" (444.50mm)	Termination	Cable (432mm) - N Female
Height (Max) 17.500" (444.50mm)	Ingress Protection	-
	Mounting Type	Bracket Mount
Applications WiMax?	Height (Max)	17.500" (444.50mm)
rippioutons "ilitax:	Applications	WiMax?
Report errors?		Report errors?

S8800B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S8800B Payment Methods





















S8800B Shipping Methods













If you have any question about S8800B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com