



S89R11DBD1-12 Information

Heisener.com

Part Number S89R11DBD1-12

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY IMPULSE DPDT 15A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S89R11DBD1-12 Specifications

Manufacturer Part Number S89R11DBD1-12 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series S89R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 533mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm) Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series S89R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 533mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	S89R11DBD1-12
Package - Series S89R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 533mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series S89R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 533mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesS89RRelay TypeImpulseCoil TypeLatching, Single CoilCoil Current533mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)15ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type Impulse Coil Type Latching, Single Coil Coil Current 533mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Latching, Single Coil Coil Current 533mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Series	S89R
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Relay Type	Impulse
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 15A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time Release Time - Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style DPDT (2 Form C) 15A 277VAC - Max 9 VDC - Logical Contact Point Poin	Coil Current	533mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style 15A 277VAC - Max 9 VDC - Insulation - Class B Chassis Mount Quick Connect - 0.250" (6.3mm)	Coil Voltage	12VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Urn Off Voltage (Min) 9 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style Cuick Connect - 0.250" (6.3mm)	Switching Voltage	277VAC - Max
Operate Time	Turn On Voltage (Max)	9 VDC
Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

S89R11DBD1-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S89R11DBD1-12 Payment Methods



















S89R11DBD1-12 Shipping Methods













If you have any question about S89R11DBD1-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com