

## S8JX-P10005 Information

Heisener.com

Part Number S8JX-P10005

Manufacturer Omron Automation and Safety

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 5V 100W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# S8JX-P10005 Specifications

Manufacturer         Omron Automation and Safety           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         S8JX-P           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         100W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         78%           Operating Temperature         -10°C ~ 70°C           Features         Load Sharing, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         S8JX-P           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         100W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         78%           Operating Temperature         -10°C ~ 70°C           Features         Load Sharing, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Manufacturer Part Number	S8JX-P10005
AC DC Converters           Package         -           Series         S8JX-P           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         100W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         78%           Operating Temperature         -10°C ~ 70°C           Features         Load Sharing, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Manufacturer	Omron Automation and Safety
Package         -           Series         S8JX-P           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         100W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         78%           Operating Temperature         -10°C ~ 70°C           Features         Load Sharing, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         S8JX-P           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         100W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         78%           Operating Temperature         -10°C ~ 70°C           Features         Load Sharing, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         100W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         78%           Operating Temperature         -10°C ~ 70°C           Features         Load Sharing, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Package	-
Number of Outputs       1         Voltage - Input       85 ~ 264 VAC         Voltage - Output 1       5V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       100W         Applications       ITE (Commercial)         Voltage - Isolation       -         Efficiency       78%         Operating Temperature       -10°C ~ 70°C         Features       Load Sharing, Universal Input         Mounting Type       Chassis Mount         Size / Dimension       6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Series	S8JX-P
Voltage - Input       85 ~ 264 VAC         Voltage - Output 1       5V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       100W         Applications       ITE (Commercial)         Voltage - Isolation       -         Efficiency       78%         Operating Temperature       -10°C ~ 70°C         Features       Load Sharing, Universal Input         Mounting Type       Chassis Mount         Size / Dimension       6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Type	Enclosed
Voltage - Output 1         5V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         100W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         78%           Operating Temperature         -10°C ~ 70°C           Features         Load Sharing, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  - Efficiency  78%  Operating Temperature  -10°C ~ 70°C  Features  Load Sharing, Universal Input  Mounting Type  Size / Dimension  - Current - Output (Max)  - Current - Output (Max)  - Commercial)  - Commercial  - Commercia	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  - Efficiency  Operating Temperature  Features  Load Sharing, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Compared Size / Dimension  - Compared Size / Output 4  - Output 4  - Output (Max)  - Out	Voltage - Output 1	5V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  78%  Operating Temperature  -10°C ~ 70°C  Features  Load Sharing, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -  Current - Output (Max)  -  20A  -  100W  -  100W  -  78%  -  100W	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  78%  Operating Temperature  -10°C ~ 70°C  Features  Load Sharing, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  20A  20A  20A  20B  Commercial  -10°C  -20°C  Load Sharing, Universal Input  Chassis Mount  6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  Operating Temperature  -10°C ~ 70°C  Features  Load Sharing, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  100W  -100W  -100	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation -  Efficiency 78%  Operating Temperature -10°C ~ 70°C  Features Load Sharing, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Current - Output (Max)	20A
Voltage - Isolation -  Efficiency 78%  Operating Temperature -10°C ~ 70°C  Features Load Sharing, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Power (Watts)	100W
Efficiency 78%  Operating Temperature -10°C ~ 70°C  Features Load Sharing, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Applications	ITE (Commercial)
Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Load Sharing, Universal Input  Mounting Type Chassis Mount  Size / Dimension $6.32^{\circ}\text{L} \times 1.65^{\circ}\text{W} \times 3.62^{\circ}\text{H} (160.5\text{mm} \times 42.0\text{mm} \times 92.0\text{mm})$	Voltage - Isolation	-
Features Load Sharing, Universal Input  Mounting Type Chassis Mount  Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Efficiency	78%
Mounting Type Chassis Mount Size / Dimension Chassis Mount 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Operating Temperature	-10°C ~ 70°C
Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Features	Load Sharing, Universal Input
· · · · · · · · · · · · · · · · · · ·	Mounting Type	Chassis Mount
	Size / Dimension	6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)
Report errors		Report errors?

### S8JX-P10005 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## S8JX-P10005 Payment Methods



















## S8JX-P10005 Shipping Methods













If you have any question about S8JX-P10005, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com