



S8JX-P10012C Information

Heisener.com

Part Number S8JX-P10012C

Manufacturer Omron Automation and Safety

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 12V 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S8JX-P10012C Specifications

Manufacturer Omron Automation and Safety Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series S8JX-P Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series S8JX-P Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Manufacturer Part Number	S8JX-P10012C	
AC DC Converters Package - Series S8IX-P Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Manufacturer	Omron Automation and Safety	
Package - Series \$8JX-P Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series S8JX-P Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Package	-	
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Series	S8JX-P	
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Туре	Enclosed	
Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Size / Dimension - Current - Output (Max)	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Voltage - Output 1	12V	
Voltage - Output 4 Current - Output (Max) 8.5A Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 8.5A 100W 78W 78W 78W 78W 78W 78W 78W	Voltage - Output 2	-	
Current - Output (Max) 8.5A Power (Watts) 100W Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 100W -100W -100W -100W -100W -100W -100C -100	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Current - Output (Max)	8.5A	
Voltage - Isolation - Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Power (Watts)	100W	
Efficiency 78% Operating Temperature -10°C ~ 70°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Applications	ITE (Commercial)	
Operating Temperature $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension $6.32^{\circ}\text{L} \times 1.65^{\circ}\text{W} \times 3.62^{\circ}\text{H} (160.5\text{mm} \times 42.0\text{mm} \times 92.0\text{mm})$	Voltage - Isolation	-	
Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Efficiency	78%	
Mounting Type Chassis Mount Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Operating Temperature	-10°C ~ 70°C	
Size / Dimension 6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	Features	Load Sharing, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	6.32" L x 1.65" W x 3.62" H (160.5mm x 42.0mm x 92.0mm)	
Report citors:			Report errors?

S8JX-P10012C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S8JX-P10012C Payment Methods



















S8JX-P10012C Shipping Methods













If you have any question about S8JX-P10012C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com