

### S8VS-48024-F Information

Heisener.com

Part Number S8VS-48024-F

Manufacturer Omron Automation and Safety

**Category** Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 24V 480W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# S8VS-48024-F Specifications

Manufacturer Part Number         S8VS-48024-F           Manufacturer         Omron Automation and Safety           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         S8VS           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)           Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         S8VS           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Manufacturer Part Number	S8VS-48024-F
Package         -           Series         S8VS           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Manufacturer	Omron Automation and Safety
Package         -           Series         S8VS           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         S8VS           Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Package	-
Number of Outputs       1         Voltage - Input       100 ~ 240 VAC         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       480W         Applications       ITE (Commercial)         Voltage - Isolation       3kV (3000V)         Efficiency       80%         Operating Temperature       -10°C ~ 60°C (With Derating)         Features       Adjustable Output, Universal Input         Mounting Type       DIN Rail         Size / Dimension       5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Series	S8VS
Voltage - Input         100 ~ 240 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         480W           Applications         ITE (Commercial)           Voltage - Isolation         3kV (3000V)           Efficiency         80%           Operating Temperature         -10°C ~ 60°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Type	Enclosed
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  DIN Rail  Size / Dimension  24V  24V  24V  24V  24V   Current - Output (Max)   20A  480W  480W  480W  480W  480W  Applications  ITE (Commercial)  3kV (3000V)  Efficiency  80%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  DIN Rail  Size / Dimension  5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  DIN Rail  Size / Dimension  Size / Dimension  Dividence of the second of the secon	Voltage - Input	100 ~ 240 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  DIN Rail  Size / Dimension  - Output 4  - Current - Output (Max)  - Current - Outpu	Voltage - Output 1	24V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  80%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  DIN Rail  Size / Dimension  -10°C ~ 5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  3kV (3000V)  Efficiency  80%  Operating Temperature  -10°C ~ 60°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  DIN Rail  Size / Dimension  5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Voltage - Output 3	-
Power (Watts) $480W$ ApplicationsITE (Commercial)Voltage - Isolation $3kV$ (3000V)Efficiency $80\%$ Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeDIN RailSize / Dimension $5.01$ " L x $5.91$ " W x $4.53$ " H (127.2mm x $150.1$ mm x $115.0$ mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation $3kV (3000V)$ Efficiency $80\%$ Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)  Features Adjustable Output, Universal Input  Mounting Type DIN Rail  Size / Dimension $5.01^{\circ}\text{L x } 5.91^{\circ}\text{W x } 4.53^{\circ}\text{H } (127.2\text{mm x } 150.1\text{mm x } 115.0\text{mm})$	Current - Output (Max)	20A
Voltage - Isolation $3kV (3000V)$ Efficiency $80\%$ Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating) Features Adjustable Output, Universal Input Mounting Type DIN Rail Size / Dimension $5.01^{\circ}\text{L x } 5.91^{\circ}\text{W x } 4.53^{\circ}\text{H } (127.2\text{mm x } 150.1\text{mm x } 115.0\text{mm})$	Power (Watts)	480W
Efficiency 80%  Operating Temperature -10°C ~ 60°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type DIN Rail  Size / Dimension 5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Applications	ITE (Commercial)
Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)  Features Adjustable Output, Universal Input  Mounting Type DIN Rail  Size / Dimension $5.01^{\circ}\text{L x } 5.91^{\circ}\text{W x } 4.53^{\circ}\text{H } (127.2\text{mm x } 150.1\text{mm x } 115.0\text{mm})$	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, Universal Input  Mounting Type DIN Rail  Size / Dimension 5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Efficiency	80%
Mounting Type DIN Rail Size / Dimension 5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)	Features	Adjustable Output, Universal Input
	Mounting Type	DIN Rail
Report errors?	Size / Dimension	5.01" L x 5.91" W x 4.53" H (127.2mm x 150.1mm x 115.0mm)
		Report errors?

#### S8VS-48024-F Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## S8VS-48024-F Payment Methods





















## S8VS-48024-F Shipping Methods













If you have any question about S8VS-48024-F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com