



S90R11ABD1-240 Information

Heisener.com

Part Number S90R11ABD1-240

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY IMPULSE DPDT 20A 240V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









S90R11ABD1-240 Specifications

Manufacturer Part Number \$90R11ABD1-240 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series \$90R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 38mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm) Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series S90R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 38mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	S90R11ABD1-240
Package - Series \$90R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 38mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series S90R Relay Type Impulse Coil Type Latching, Single Coil Coil Current 38mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Category	Relays
SeriesS90RRelay TypeImpulseCoil TypeLatching, Single CoilCoil Current38mACoil Voltage240VACContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay Type Impulse Coil Type Latching, Single Coil Coil Current 38mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Latching, Single Coil Coil Current 38mA Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Series	S90R
Coil Current Coil Voltage 240VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 20A Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Relay Type	Impulse
Coil Voltage240VACContact FormDPDT (2 Form C)Contact Rating (Current)20ASwitching Voltage277VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleQuick Connect - 0.250" (6.3mm)	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style DPDT (2 Form C) 20A 20A 277VAC - Max 204 VAC - Insulation - Class B Quick Connect - 0.250" (6.3mm)	Coil Current	38mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style 20A 277VAC - Max 204 VAC - Insulation - Class B Quick Connect - 0.250" (6.3mm)	Coil Voltage	240VAC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) Operate Time Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	20A
Turn Off Voltage (Min) Operate Time Release Time Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Switching Voltage	277VAC - Max
Operate Time	Turn On Voltage (Max)	204 VAC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Quick Connect - 0.250" (6.3mm)
		Report errors?

S90R11ABD1-240 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

S90R11ABD1-240 Payment Methods



















S90R11ABD1-240 Shipping Methods













If you have any question about S90R11ABD1-240, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com