

SA2404 Information

Heisener.com

Part Number SA2404 Manufacturer Bulgin

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 3POS PNL MNT SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SA2404 Specifications

Manufacturer Part NumberSA2404ManufacturerBulginCategoryConnectors, InterconnectsPackage-SeriesGeneral PurposeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishNylon, Glass FilledContact FinishTinFeatures-Voltage - Rated250VACCurrent Rating3A		
Category Connectors, Interconnects Circular Connectors Package - Series General Purpose Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Nylon, Glass Filled Contact Finish Tin Features - Voltage - Rated Current Rating 3A	Manufacturer Part Number	SA2404
Package-SeriesGeneral PurposeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishNylon, Glass FilledContact FinishTinFeatures-Voltage - Rated250VACCurrent Rating3A	Manufacturer	Bulgin
Package-SeriesGeneral PurposeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishNylon, Glass FilledContact FinishTinFeatures-Voltage - Rated250VACCurrent Rating3A	Category	Connectors, Interconnects
SeriesGeneral PurposeConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishNylon, Glass FilledContact FinishTinFeatures-Voltage - Rated250VACCurrent Rating3A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishNylon, Glass FilledContact FinishTinFeatures-Voltage - Rated250VACCurrent Rating3A	Package	-
Number of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishNylon, Glass FilledContact FinishTinFeatures-Voltage - Rated250VACCurrent Rating3A	Series	General Purpose
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Nylon, Glass Filled Contact Finish Tin Features - Voltage - Rated Current Rating 3A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Nylon, Glass Filled Contact Finish Tin Features - Voltage - Rated Current Rating 3A	Number of Positions	3
Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationSolder CupFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishNylon, Glass FilledContact FinishTinFeatures-Voltage - Rated250VACCurrent Rating3A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Nylon, Glass Filled Contact Finish Tin Features - Voltage - Rated 250VAC Current Rating 3A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Nylon, Glass Filled Contact Finish Tin Features - Voltage - Rated 250VAC Current Rating 3A	Mounting Type	Panel Mount, Bulkhead - Rear Side Nut
Orientation Keyed Ingress Protection - Shell Material, Finish Nylon, Glass Filled Contact Finish Tin Features - Voltage - Rated 250VAC Current Rating 3A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Nylon, Glass Filled Contact Finish Tin Features - Voltage - Rated 250VAC Current Rating 3A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Tin Features - Voltage - Rated Current Rating Shell Material, Finish Tin 3A	Orientation	Keyed
Contact Finish Tin Features - Voltage - Rated 250VAC Current Rating 3A	Ingress Protection	-
Features - Voltage - Rated 250VAC Current Rating 3A	Shell Material, Finish	Nylon, Glass Filled
Voltage - Rated 250VAC Current Rating 3A	Contact Finish	Tin
Current Rating 3A	Features	-
-	Voltage - Rated	250VAC
Report errors?	Current Rating	3A
		Report errors?

SA2404 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SA2404 Payment Methods



















SA2404 Shipping Methods













If you have any question about SA2404, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com