



SA305C154MAA Information



For Reference Only

Part Number SA305C154MAA
Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.15UF 50V X7R AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SA305C154MAA Specifications

Manufacturer Part Number SA305C154MAA Manufacturer AVX Corporation Category Capacitors Package Axial Series SpinGuard? SA Capacitance 0.15μF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series SpinGuard? SA Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Manufacturer Part Number	SA305C154MAA
Package Axial Series SpinGuard? SA Capacitance 0.15μF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Manufacturer	AVX Corporation
Package Axial Series SpinGuard? SA Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Category	Capacitors
Series SpinGuard? SA Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -		Ceramic Capacitors
Capacitance 0.15μF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Package	Axial
Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) Lead Spacing	Series	SpinGuard? SA
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.290" L (3.81mm x 7.37mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-	Capacitance	0.15μF
Temperature Coefficient A7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing X7R A7R A7R A7R A7R - Size / Dimension A7R A7R - Size / Dimension A7R A7R A7R A7R A7R A7R A7R A7	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.290" L (3.81mm x 7.37mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-	Voltage - Rated	50V
Features - General Purpose - General Purpose - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - General Purpose - G	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Lead Spacing	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Applications	General Purpose
Package / Case Axial Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Failure Rate	-
Size / Dimension 0.150" Dia x 0.290" L (3.81mm x 7.37mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Package / Case	Axial
Thickness (Max) - Lead Spacing -	Size / Dimension	0.150" Dia x 0.290" L (3.81mm x 7.37mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	-
Lead Style -	Lead Spacing	-
·	Lead Style	-
Report errors?		Report errors?

SA305C154MAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SA305C154MAA Payment Methods





















SA305C154MAA Shipping Methods













If you have any question about SA305C154MAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com