



SA401A472FAA Information

Heisener.com

Part Number SA401A472FAA Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

CAP CER 4700PF 100V NP0 AXIAL **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SA401A472FAA Specifications

Manufacturer Part Number SA401A472FAA Manufacturer AVX Corporation Category Capacitors Package Axial Series SpinGuard? SA Capacitance 4700pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series SpinGuard? SA Capacitance 4700pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	SA401A472FAA
Package Axial Series SpinGuard? SA Capacitance 4700pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package Axial Series SpinGuard? SA Capacitance 4700pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series SpinGuard? SA Capacitance 4700pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 4700pF Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±1% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Lead Style Tough Hole Lead Style Lead Style Lead Style Lead Style Tough Hole Lead Style Le	Series	SpinGuard? SA
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	4700pF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Tolerance	±1%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Voltage - Rated	100V
Features - Cartes - C	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Mount of the state of	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Applications	General Purpose
Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.150" Dia x 0.400" L (3.81mm x 10.16mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

SA401A472FAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SA401A472FAA Payment Methods



















SA401A472FAA Shipping Methods













If you have any question about SA401A472FAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com