

SA401A682KAA

SA401A682KAA Information

Heisener.com	 SA401A682KAA AVX Corporation Capacitors Ceramic Capacitors CAP CER 6800PF 100V NP0 AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SA401A682KAA Specifications

Manufacturer Part Number SA401A682KAA Manufacturer AVX Corporation Category Capacitors Package Axial Package SpinGurd's SA Capacitance 6800pF Tolerance ±10% Voltage - Rated 00V Tomperature Coefficient 00V Opting Temperature -55°C ~ 125°C Pactage - Applications - Applications - Applications - Pactage - Applications General Purpose Applications - Applications - Package / Case - Applications - Applications - Package / Case - Applications	-	
Catagory Capacitors Package Axial Series SpinGuard? SA Capacitance 6800pF Catagory 10% Yoltage - Rated 100V Yoltage - Rated 00V Operating Temperature Coefficient 00G, NP0 Pactargy -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type General Purpose Package / Case Axial Size / Dimension 0.150° Dia x 0.400° L (3.81mm x 10.16mm) Height - Seated (Max) - Height - Seated (Max) <t< td=""><td>Manufacturer Part Number</td><td>SA401A682KAA</td></t<>	Manufacturer Part Number	SA401A682KAA
Ceramic CapacitorsPackageAxialSeriesSpinGuard? SACapacitance6800pFTolerance±10%Voltage - Rated100VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.150° Di ax 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	AVX Corporation
PackageAxialSeriesSpinGuard? SACapacitance6800pFTolerance±10%Voltage Rated100VTemperature CoefficientCOG, NPOOperating Temperature-5°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Noutring TypeMialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Size / Dimension-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-Starter<	Category	Capacitors
Series SpinGuard? SA Capacitance 6800pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Mounting Type - Package / Case Axial Size / Dimension 0.150° Dia x 0.400° L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
CapacitanceBoopFTolerance±10%Voltage - Rated100VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Package	Axial
Tolerance±10°Voltage - Rated100VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeHolePackage / CaseAxialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing-Lead Style-Stare Style-Stare Style-Stare Style-Style <td>Series</td> <td>SpinGuard? SA</td>	Series	SpinGuard? SA
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeHolePackage / CaseAxialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing-Lead Spacing-Height Seated (Max)-Height Seated (Max)-<	Capacitance	6800pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleStack ge / Case0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.150° Dia ConstructionLead Style-State Style-State Style-State Style-State Style-Style	Tolerance	$\pm 10\%$
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.Lead Style-Star (Style-Star (Sty	Voltage - Rated	100V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting Type-Package / CaseArialSize / Dimension0.150" Dia x 0.400" L (0.31 mm x 10.16 mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Head Style-Head Style-Hea	Temperature Coefficient	C0G, NP0
Ratings-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Starter Max-Starter Max- </td <td>Operating Temperature</td> <td>-55°C ~ 125°C</td>	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Height - Seated (Max)<	Ratings	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Output-Style-	Applications	General Purpose
Package / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Package / Case	Axial
Thickness (Max)-Lead Spacing-Lead Style-	Size / Dimension	0.150" Dia x 0.400" L (3.81mm x 10.16mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

SA401A682KAA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SA401A682KAA Payment Methods



SA401A682KAA Shipping Methods



If you have any question about SA401A682KAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com