

# SA405C154JAR

#### SA405C154JAR Information

Contact levice statution	SA405C154JAR AVX Corporation Capacitors Ceramic Capacitors CAP CER 0.15UF 50V X7R AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# SA405C154JAR Specifications

ManufacturerAVX CorporationCapacitorsCeramic CapacitorsPackageAxialSeriesSpinGuard? SACapacitance.15µFTolerance±5%Voltage - RatedSOVTomperature CoefficientX7ROperating Temperature.5°°C ~ 125°CPackage.6Ratings.6Failure Rate.6Mounting TypeGeneral PurposePackage / Case.4xialSize / Dimension.150° Di ax 0.400° L (3.81mm x 10.16mm)Height - Seated (Max).6Height - Seated (Max).6Height - Seated (Max).6Lead Spacing.5Lead SyleSriaght		
Capacitors   Package Axial   Series SpinGuard? SA   Capacitors 0.15µF   Tolerance 5% 0.15µF   Voltage - Rated 50V   Speries 50V   Copaciting Coefficient 50°C ~ 125°C ~ 125°C   Operating Temperature -   Splications General Purpose   Applications General Purpose   Failure Rate -   Mounting Type String Hole   Size / Dimension 0.150°D iau a.0400° L (3.81mm x 10.16mm)   Size / Dimension -   Height - Seated (Max) -   Height Seated (Max) -   Lead Syle Stringht	Manufacturer Part Number	SA405C154JAR
Ceramic CapacitorsPackageAxialSeriesSpinGuard? SACapacitance0.15µFTolerance±5%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-5°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead StyleStraight	Manufacturer	AVX Corporation
PackageAxialSeriesSpinGuard? SACapacitance0.15µFTolerance±5%Voltage - Rated50VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead StyleStraight	Category	Capacitors
Series SpinGuard? SA   Capacitance 0.15μF   Tolerance ±5%   Voltage - Rated 50V   Tomperature Coefficient X7R   Operating Temperature -55°C ~ 125°C   Features -   Ratings -   Applications General Purpose   Failure Rate -   Mounting Type Through Hole   Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm)   Height - Seated (Max) -   Thickness (Max) -   Lead Spacing -   Lead Style Straight		Ceramic Capacitors
Capacitance0.15µFTolerance±5%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingStraight	Package	Axial
Tolerance±5%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead StyleStraight	Series	SpinGuard? SA
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Height Gase-Lead SpacingStraightLead StyleStraight	Capacitance	0.15µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingStraight	Tolerance	$\pm 5\%$
Operating Temperature-55°C ~ 125°CFeatures-Ratings-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingStraight	Voltage - Rated	50V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Kead StyleStraight	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Kead StyleStraightKead StyleStraight	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Applications	General Purpose
Package / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Failure Rate	-
Size / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Mounting Type	Through Hole
Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Package / Case	Axial
Thickness (Max)-Lead Spacing-Lead StyleStraight	Size / Dimension	0.150" Dia x 0.400" L (3.81mm x 10.16mm)
Lead Spacing-Lead StyleStraight	Height - Seated (Max)	-
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	Straight
		Report errors?

#### SA405C154JAR Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### SA405C154JAR Payment Methods





If you have any question about SA405C154JAR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com