



SA405C154MAA Information

Heisener.com

Part Number SA405C154MAA Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.15UF 50V X7R AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SA405C154MAA Specifications

Manufacturer Part Number SA405C154MAA Manufacturer AVX Corporation Category Capacitors Package Axial Series SpinGuard? SA Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series SpinGuard? SA Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	SA405C154MAA
Package Axial Series SpinGuard? SA Capacitance 0.15μF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package Axial Series SpinGuard? SA Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series SpinGuard? SA Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.15µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Series	SpinGuard? SA
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	0.15μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	50V
Features - Cartes - C	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Lead Spacing - Lead Style - Case -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Mount of the seated in the seated i	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case Axial Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.150" Dia x 0.400" L (3.81mm x 10.16mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

SA405C154MAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SA405C154MAA Payment Methods



















SA405C154MAA Shipping Methods













If you have any question about SA405C154MAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com