

SA405C224MAA

SA405C224MAA Information

Contract territors and they	 SA405C224MAA AVX Corporation Capacitors Ceramic Capacitors CAP CER 0.22UF 50V X7R AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SA405C224MAA Specifications

Manufacturer Part Number SA405C224MAA Manufacturer AVX Corporation Category Capacitors Package Axial Series SpinGuard? SA Capacitance 0.22µF Yoltage - Rated 50° Operating Temperature So°C > 215°C Operating Temperature - Applications General Purpose Mounting Type Nongh Hole Yoltage / Case Axial Size / Dimension 0.150° Dia x 0.400° L (3.81mm x 10.16mm) Height - Seated (Max) - Height Seated (Max) - Lead Spacing - Lead Spacing -		
Action Capacitors Package Axial Series SpinGuard? SA Capacitance 0.22 µF Tolerance ±20% Voltage - Rated 50 V Tomperature Coefficient StrR Operating Temperature -55°C ~ 125°C Ratings - Applications General Purpose Pailure Rate - Mounting Type General Purpose Package / Case Axial Size / Dimension 1.50°C hold on the state	Manufacturer Part Number	SA405C224MAA
Ceramic CapacitorsPackageAxialSeriesSpinGuard? SACapacitance0.22µFTolerance±20%Voltage - RatedSoVTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.50°Di ax 0.400°L (3.81mm x 10.16mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	AVX Corporation
PackageAxialSeriesSpinGuard? SACapacitance0.22µFTolerance±20%Voltage - RatedSoVTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-ApplicationsGeneral PurposeApplicationsGeneral PurposeFailure Rate-Nounting TypeAxialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Category	Capacitors
Series SpinGuard? SA Capacitance 0.22µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Mounting Type Mough Hole Size / Dimension 0.150° Dia x 0.400° L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.22µF Tolerance ±20% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Size / Dimension 0.150° Dia x 0.400° L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance±20%Voltage - Rated50VTemperature CoefficientXTROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeHolePackage / Case.150° Dia x 0.400° L (3.81mm x 10.16mm)Size / Dimension-Height - Seated (Max)-Lead Spacing-Lead Style- <td>Series</td> <td>SpinGuard? SA</td>	Series	SpinGuard? SA
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeMindePackage / CaseAxialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing-Lead Spacing-Height Seated (Max)-Height Seated (Max)-<	Capacitance	0.22µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSackage / CaseAxialSize / Dimension0.150° Dia x 0.400° L (3.81mm x 10.16mm)Height - Seated (Max)-Fackage fully-Lead Spacing-Lead Spacing-Starter Starter-Starter Starter-Starter-Starter-<	Tolerance	±20%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.Lead Style-Star Dimension-Star Dimension-	Voltage - Rated	50V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting Type-Package / CaseAxialSize / Dimension0.150" Dia x 0.400" L (0.38 Imm x 10.16 mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Head Style-Head Style-He	Temperature Coefficient	X7R
Ratings-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (0.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Starter Max-Starter Max- </td <td>Operating Temperature</td> <td>-55°C ~ 125°C</td>	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81 mm x 10.16 mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Starter Style-Starter Style-Starter Style-Starter Style-Style	Ratings	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Output-Style-	Applications	General Purpose
Package / CaseAxialSize / Dimension0.150" Dia x 0.400" L (3.81mm x 10.16mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.150" Dia x 0.400" L (3.81mm x 10.16mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Package / Case	Axial
Thickness (Max)-Lead Spacing-Lead Style-	Size / Dimension	0.150" Dia x 0.400" L (3.81mm x 10.16mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
· ·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

SA405C224MAA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SA405C224MAA Payment Methods



SA405C224MAA Shipping Methods



If you have any question about SA405C224MAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com