

SA64 Information

www.helenner.com

For Reference Only

Part Number SA64

Manufacturer Littelfuse Inc.

Category Circuit Protection
TVS - Diodes

Description TVS DIODE 64VWM 108.15VC DO204AC

Package DO-204AC, DO-15, Axial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SA64 Specifications

Manufacturer Part Number \$A64 Manufacturer Littelfuse Inc. Category Circuit Protection TVS - Diodes Package DO-204AC, DO-15, Axial Series SA Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 64V Voltage - Breakdown (Min) 67.37V Voltage - Clamping (Max) @ Ipp 108.15V Current - Peak Pulse (10/1000µs) 5A Power - Peak Pulse 500W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TI) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	*	
Category Circuit Protection TVS - Diodes Package DO-204AC, DO-15, Axial Series SA Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 64V Voltage - Breakdown (Min) 67.37V Voltage - Clamping (Max) @ Ipp 108.15V Current - Peak Pulse (10/1000µs) 5A Power - Peak Pulse 500W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	Manufacturer Part Number	SA64
Package DO-204AC, DO-15, Axial Series SA Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 64V Voltage - Breakdown (Min) 67.37V Voltage - Clamping (Max) @ Ipp 108.15V Current - Peak Pulse (10/1000μs) 5A Power - Peak Pulse 500W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	Manufacturer	Littelfuse Inc.
PackageDO-204AC, DO-15, AxialSeriesSATypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)64VVoltage - Breakdown (Min)67.37VVoltage - Clamping (Max) @ Ipp108.15VCurrent - Peak Pulse (10/1000μs)5APower - Peak Pulse500WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-204AC (DO-15)	Category	Circuit Protection
SeriesSATypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)64VVoltage - Breakdown (Min)67.37VVoltage - Clamping (Max) @ Ipp108.15VCurrent - Peak Pulse (10/1000μs)5APower - Peak Pulse500WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-204AC (DO-15)		TVS - Diodes
Type Zener Unidirectional Channels 1 Bidirectional Channels - Voltage - Reverse Standoff (Typ) 64V Voltage - Breakdown (Min) 67.37V Voltage - Clamping (Max) @ Ipp 108.15V Current - Peak Pulse (10/1000µs) 5A Power - Peak Pulse So0W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package	Package	DO-204AC, DO-15, Axial
Unidirectional Channels Bidirectional Channels Voltage - Reverse Standoff (Typ) 64V Voltage - Breakdown (Min) 67.37V Voltage - Clamping (Max) @ Ipp 108.15V Current - Peak Pulse (10/1000µs) 5A Power - Peak Pulse 500W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package	Series	SA
Bidirectional Channels-Voltage - Reverse Standoff (Typ)64VVoltage - Breakdown (Min)67.37VVoltage - Clamping (Max) @ Ipp108.15VCurrent - Peak Pulse (10/1000μs)5APower - Peak Pulse500WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-204AC (DO-15)	Type	Zener
Voltage - Reverse Standoff (Typ)64VVoltage - Breakdown (Min)67.37VVoltage - Clamping (Max) @ Ipp108.15VCurrent - Peak Pulse (10/1000μs)5APower - Peak Pulse500WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-204AC (DO-15)	Unidirectional Channels	1
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 108.15V Current - Peak Pulse (10/1000μs) 5A Power - Peak Pulse 500W Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp Current - Peak Pulse (10/1000μs) 5A Power - Peak Pulse 500W Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package	Voltage - Reverse Standoff (Typ)	64V
Current - Peak Pulse (10/1000μs)5APower - Peak Pulse500WPower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-204AC, DO-15, AxialSupplier Device PackageDO-204AC (DO-15)	Voltage - Breakdown (Min)	67.37V
Power - Peak Pulse 500W Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	Voltage - Clamping (Max) @ Ipp	108.15V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package	Current - Peak Pulse (10/1000µs)	5A
Applications Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package	Power - Peak Pulse	500W
Capacitance @ Frequency Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	Power Line Protection	No
Operating Temperature -55°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	Applications	General Purpose
Mounting Type Through Hole Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	Capacitance @ Frequency	-
Package / Case DO-204AC, DO-15, Axial Supplier Device Package DO-204AC (DO-15)	Operating Temperature	-55°C ~ 175°C (TJ)
Supplier Device Package DO-204AC (DO-15)	Mounting Type	Through Hole
	Package / Case	DO-204AC, DO-15, Axial
Report errors?	Supplier Device Package	DO-204AC (DO-15)
		Report errors?

SA64 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SA64 Payment Methods





















SA64 Shipping Methods













If you have any question about SA64, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com