



SAN.M08.GLC.7G Information

Heisener.com

Part Number SAN.M08.GLC.7G

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description PLUG INLINE 8PIN CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SAN.M08.GLC.7G Specifications

Manufacturer Part NumberSAN.M08.GLC.7GManufacturerLEMOCategoryConnectors, InterconnectsPackage-SeriesSPConnector TypePlug, Male PinsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A		
CategoryConnectors, InterconnectsPackage-SeriesSPConnector TypePlug, Male PinsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Manufacturer Part Number	SAN.M08.GLC.7G
PackageCircular ConnectorsSeriesSPConnector TypePlug, Male PinsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Manufacturer	LEMO
Package-SeriesSPConnector TypePlug, Male PinsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Category	Connectors, Interconnects
SeriesSPConnector TypePlug, Male PinsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Package	-
Number of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Series	SP
Shell Size - InsertM08Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Push-Pull Orientation N (Normal) Ingress Protection IP50 - Dust Protected Shell Material, Finish Sulfone Contact Finish - Features Backshell Voltage - Rated - Current Rating 5A	Number of Positions	8
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypePush-PullOrientationN (Normal)Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Shell Size - Insert	M08
Termination Crimp Fastening Type Push-Pull Orientation N (Normal) Ingress Protection IP50 - Dust Protected Shell Material, Finish Sulfone Contact Finish - Features Backshell Voltage - Rated - Current Rating 5A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation N (Normal) Ingress Protection IP50 - Dust Protected Shell Material, Finish Sulfone Contact Finish - Features Backshell Voltage - Rated - Current Rating 5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP50 - Dust Protected Shell Material, Finish Sulfone Contact Finish - Features Backshell Voltage - Rated - Current Rating 5A	Termination	Crimp
Ingress Protection IP50 - Dust Protected Shell Material, Finish Sulfone Contact Finish - Features Backshell Voltage - Rated - Current Rating 5A	Fastening Type	Push-Pull
Shell Material, FinishSulfoneContact Finish-FeaturesBackshellVoltage - Rated-Current Rating5A	Orientation	N (Normal)
Contact Finish - Features Backshell Voltage - Rated - Current Rating 5A	Ingress Protection	IP50 - Dust Protected
Features Backshell Voltage - Rated - Current Rating 5A	Shell Material, Finish	Sulfone
Voltage - Rated - Current Rating 5A	Contact Finish	-
Current Rating 5A	Features	Backshell
-	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

SAN.M08.GLC.7G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SAN.M08.GLC.7G Payment Methods



















SAN.M08.GLC.7G Shipping Methods













If you have any question about SAN.M08.GLC.7G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com