

## SAR405SD

### **SAR405SD Information**



Part Number	SAR405SD	
Manufacturer	Cynergy 3	
Category	Relays Signal Relays, Up to 2 Amps	
Description	RELAY REED SPST-NO 500MA 5V	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## SAR405SD Specifications

Manufacturer Part NumberSAR405SDManufacturerCynergy 3CategoryRelaysSignal Relays, Up to 2 AmpsPackage-Series4Relay TypeReedCoil TypeNon LatchingCoil Current71.4mACoil ActionSPST-NO (I Form A)Contact FormSOMASwitching Voltage (Mary)SOVCSwitching Voltage (Mary)3.5 VDCTurn On Voltage (Mary)1.VDCOperate TimeImsRelease Time0.SmsFeatures30 MHzTurnon StylePC Pin		
CategoryRelaysSagnal Relays, Up to 2 AmpsPackage-Series4Relay TypeReedCoil TypeNon LatchingCoil Current71.4mACoil VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Max)1 VDCQerate Time0.5msRelease Time0.5msFatures30 MHzMounting TypeThrough HoleTermination Style9C Pin	Manufacturer Part Number	SAR405SD
Signal Relays, Up to 2 AmpsPackage-Series4Relay TypeReedCoil TypeNon LatchingCoil Current71.4mACoil VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCCurnent1 VDCOperate Time0.5msRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StyleCP in	Manufacturer	Cynergy 3
Package-Series4Relay TypeRedCoil TypeNon LatchingCoil Current71.4mAColl CurrentSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)SOMASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCCurrent Form1.10DCRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleFermination StyleCP in	Category	Relays
Series4Relay TypeReedCoil TypeNon LatchingCoil Current7.1.4mACoil VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)SOMASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)1 VDCOperate TimeSomsRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current71.4mACoil VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)S00mASwitching Voltage (Max)3.5 VDC - MaxTurn On Voltage (Min)1 VDCOperate TimeSomsRelayes Time0.5msFeatures3.0 MHzMounting TypeTimogational (Though Hole)Termination StyleCP (Pain	Package	-
Coil TypeNon LatchingCoil Current71.4mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCCurrent Forme1.4VDCPoerate Time0.5msRelease Time0.5msFeatures30 MHzMonting TypeTimoga (Max)Fermination StyleCP (Pin	Series	4
Coil Current71.4mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)1 VDCOperate Time1msRelease Time0.5msFeatures30 MHzMounting TypeThrough HolePremination StylePC Pin	Relay Type	Reed
Coil VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)1 VDCOperate Time1msRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)1 VDCOperate Time1msRelease Time0.5msFeatures30 MHzMounting TypeThrough HolePermination StylePC Pin	Coil Current	71.4mA
Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)1 VDCOperate TimeImsRelease Time0.5msFeatures30 MHzMounting TypeThrough HolePermination StylePC Pin	Coil Voltage	5VDC
Switching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)1 VDCOperate Time1msRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleFermination StylePC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)1 VDCOperate TimeImsRelease Time0.5 msFeatures30 MHzMounting TypeThrough HoleFermination StylePC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min)1 VDCOperate TimeImsRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	20VAC, 20VDC - Max
Operate TimeImsRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	1 VDC
Features30 MHzMounting TypeThrough HoleTermination StylePC Pin	Operate Time	lms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	0.5ms
Termination Style PC Pin	Features	30 MHz
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **SAR405SD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about SAR405SD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com