



SAR424SU Information



For Reference Only

Part Number SAR424SU
Manufacturer Cynergy 3
Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST-NO 500MA 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SAR424SU Specifications

Manufacturer Part Number SAR424SU Manufacturer Cynergy 3 Category Relays Signal Relays, Up to 2 Amps Package - Series 4 Relay Type Reed Coil Type Non Latching Coil Current 16mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time Ims Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads		
Category Relays Backage - Series 4 Relay Type Reed Coil Type Non Latching Coil Current 16mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Manufacturer Part Number	SAR424SU
Package - Series 4 Relay Type Reed Coil Type Non Latching Coil Current 16mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Manufacturer	Cynergy 3
Package - Series 4 Relay Type Reed Coil Type Non Latching Coil Current 16mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Category	Relays
Series4Relay TypeReedCoil TypeNon LatchingCoil Current16mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)4 VDCOperate TimeImsRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin, Wire Leads		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current16mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)4 VDCOperate Time1msRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin, Wire Leads	Package	-
Coil TypeNon LatchingCoil Current16mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)15 VDCTurn Off Voltage (Min)4 VDCOperate Time1msRelease Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin, Wire Leads	Series	4
Coil Current Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time Ims Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Relay Type	Reed
Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time Ims Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Coil Current	16mA
Contact Rating (Current) Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style	Coil Voltage	24VDC
Switching Voltage Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) Operate Time Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style 20VAC, 20VDC - Max 15 VDC 4 VDC 0 Max 4 VDC 1 ms 1 ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 15 VDC Turn Off Voltage (Min) 4 VDC Operate Time 1ms Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time Ims Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style 4 VDC 1ms 1ms 0.5ms 70 MHz 10 MHz 10 MHz 10 MHz 10 MHz 10 MHz 11 MHz 12 MHz 13 MHz 14 MHz 15 MHz 16 MHz 17 MHz 18 M	Switching Voltage	20VAC, 20VDC - Max
Operate Time 1ms Release Time 0.5ms Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Turn On Voltage (Max)	15 VDC
Release Time0.5msFeatures30 MHzMounting TypeThrough HoleTermination StylePC Pin, Wire Leads	Turn Off Voltage (Min)	4 VDC
Features 30 MHz Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Operate Time	1ms
Mounting Type Through Hole Termination Style PC Pin, Wire Leads	Release Time	0.5ms
Termination Style PC Pin, Wire Leads	Features	30 MHz
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Wire Leads
		Report errors?

SAR424SU Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SAR424SU Payment Methods



















SAR424SU Shipping Methods













If you have any question about SAR424SU, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com