

### **SAR91203 Information**



For Reference Only

Part Number SAR91203 Manufacturer Cynergy 3 Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **SAR91203 Specifications**

Manufacturer Part NumberSAR91203ManufacturerCynergy 3CategoryRelaysPackage-SeriesSRelay TypeReedCoil TypeNon LatchingCoil Current20mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.25 VDCOperate TimeImsRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesSRelay TypeReedCoil TypeNon LatchingCoil Current20mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.25 VDCOperate Time1msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	SAR91203
Package-SeriesSRelay TypeReedCoil TypeNon LatchingCoil Current20mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.25 VDCOperate TimeImsRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Cynergy 3
Package-SeriesSRelay TypeReedCoil TypeNon LatchingCoil Current20mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.25 VDCOperate TimeImsRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesSRelay TypeReedCoil TypeNon LatchingCoil Current20mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.25 VDCOperate Time1msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current20mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.25 VDCOperate Time1 msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current20mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage20VAC, 20VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.25 VDCOperate Time1msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	S
Coil Current 20mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.25 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.25 VDC Operate Time Ims Release Time 0.5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 20VAC, 20VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.25 VDC Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	20mA
Contact Rating (Current)  Switching Voltage  20VAC, 20VDC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  1.25 VDC  Operate Time  1ms  Release Time  0.5ms  Features  - Mounting Type  Through Hole  Termination Style	Coil Voltage	12VDC
Switching Voltage 20VAC, 20VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 1.25 VDC  Operate Time 1ms  Release Time 0.5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  9 VDC  1.25 VDC  Operate Time  1 ms  Release Time  0.5 ms  Features  - Mounting Type  Through Hole  Termination Style  9 VDC  1.25 VDC  1 ms  1 ms  P. D. Sms  P. D. Sms  P. D. Sms  P. D. Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  Ims  Release Time  0.5ms  Features  Mounting Type  Through Hole  Termination Style  1.25 VDC  1ms  Temporate Time  1.25 VDC  1ms  Possible  Temporate Time  Possible  PC Pin	Switching Voltage	20VAC, 20VDC - Max
Operate Time 1ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9 VDC
Release Time 0.5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Turn Off Voltage (Min)	1.25 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	1ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.5ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **SAR91203 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **SAR91203 Payment Methods**





















## **SAR91203 Shipping Methods**













If you have any question about SAR91203, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com