

## SBLB25L30CT-E3/81

#### SBLB25L30CT-E3/81 Information

www.hasener.com	 SBLB25L30CT-E3/81 Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE ARRAY SCHOTTKY 30V TO263AB TO-263-3, D2Pak (2 Leads + Tab), TO-263AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### SBLB25L30CT-E3/81 Specifications

Manufacturer Part NumberSBLB25130CT-E3/81ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsPackageTo-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Jo) (per Diode)12.5ASpeedFast Recovery =< 500ns, > 200mA (Jo)SpeedShotkyCurrent - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction-55°C ~ 150°CMonting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB			
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If490mV @ 12.5ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Manufacturer Part Number	SBLB25L30CT-E3/81	
Diodes - Rectifiers - ArraysPackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If490mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Manufacturer	Vishay Semiconductor Diodes Division	
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If490mV @ 12.5ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Category	Discrete Semiconductor Products	
Series -   Diode Configuration 1 Pair Common Cathode   Diode Type Schottky   Voltage - DC Reverse (Vr) (Max) 30V   Current - Average Rectified (Io) (per Diode) 12.5A   Voltage - Forward (Vf) (Max) @ If 490mV @ 12.5A   Speed Fast Recovery = < 500ns, > 200mA (Io)   Reverse Recovery Time (trr) -   Current - Reverse Leakage @ Vr 900µA @ 30V   Operating Temperature - Junction -55°C ~ 150°C   Mounting Type Surface Mount   Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB		Diodes - Rectifiers - Arrays	
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If490mV @ 12.5ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB	
Diode Type Schottky   Voltage - DC Reverse (Vr) (Max) 30V   Current - Average Rectified (Io) (per Diode) 12.5A   Voltage - Forward (Vf) (Max) @ If 490mV @ 12.5A   Speed Fast Recovery = < 500ns, > 200mA (Io)   Reverse Recovery Time (trr) -   Current - Reverse Leakage @ Vr 900μA @ 30V   Operating Temperature - Junction -55°C ~ 150°C   Mounting Type Surface Mount   Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Series	-	
Voltage - DC Reverse (Vr) (Max) 30V   Current - Average Rectified (Io) (per Diode) 12.5A   Voltage - Forward (Vf) (Max) @ If 490mV @ 12.5A   Speed Fast Recovery = < 500ns, > 200mA (Io)   Reverse Recovery Time (trr) -   Current - Reverse Leakage @ Vr 900μA @ 30V   Operating Temperature - Junction -55°C ~ 150°C   Mounting Type Surface Mount   Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Diode Configuration	1 Pair Common Cathode	
Current - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If490mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Diode Type	Schottky	
Voltage - Forward (Vf) (Max) @ If490mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Voltage - DC Reverse (Vr) (Max)	30V	
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900µA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Current - Average Rectified (Io) (per Diode)	12.5A	
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr900μA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Voltage - Forward (Vf) (Max) @ If	490mV @ 12.5A	
Current - Reverse Leakage @ Vr900μA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Speed	Fast Recovery =< 500ns, > 200mA (Io)	
Operating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Reverse Recovery Time (trr)	-	
Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Current - Reverse Leakage @ Vr	900µA @ 30V	
Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB	Operating Temperature - Junction	-55°C ~ 150°C	
	Mounting Type	Surface Mount	
	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB	
Supplier Device Package TO-263AB	Supplier Device Package	TO-263AB	
Report errors?		Report errors?	

#### SBLB25L30CT-E3/81 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### SBLB25L30CT-E3/81 Payment Methods





If you have any question about SBLB25L30CT-E3/81, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com