

SBM1040CT-13-F

SBM1040CT-13-F Information

er.com

Part Number	SBM1040CT-13-F	
Manufacturer	Diodes Incorporated	
Category	Discrete Semiconductor Products Diodes - Rectifiers - Arrays	
Description	DIODE SCHKY 40V 5A POWERMITE3	
Package	Powermite?3	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	





For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SBM1040CT-13-F Specifications

Manufacturer Part NumberSBM1040CT-13-FManufacturerDiddes IncorporatedCategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackagePowernite?3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo) (per Diode)5ASpeedFast Recovery Time (trr)Speed-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - Junction55°C ~ 150°CMounting TypeSurface MountPackage / CasePowernite?3Supplier Device PackagePowernite?3		
CategoryDiscrete Semiconductor ProductsCategoryDiodes - Rectifiers - ArraysPackagePowermite?3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - JunctionSurface MountMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Manufacturer Part Number	SBM1040CT-13-F
Diodes - Rectifiers - ArraysPackagePowermite?3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - JunctionSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite?3	Manufacturer	Diodes Incorporated
PackagePowermite?3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Package	Powermite?3
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackageForward (Strict Strict	Series	-
Voltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)5AVoltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150μA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If480mV @ 5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150μA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Voltage - DC Reverse (Vr) (Max)	40V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150μA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Current - Average Rectified (Io) (per Diode)	5A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr150µA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Voltage - Forward (Vf) (Max) @ If	480mV @ 5A
Current - Reverse Leakage @ Vr150μA @ 35VOperating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CasePowermite?3Supplier Device PackagePowermite 3	Current - Reverse Leakage @ Vr	150µA @ 35V
Package / CasePowermite?3Supplier Device PackagePowermite 3	Operating Temperature - Junction	-55°C ~ 150°C
Supplier Device Package Powermite 3	Mounting Type	Surface Mount
	Package / Case	Powermite?3
	Supplier Device Package	Powermite 3
Report error		Report errors?

SBM1040CT-13-F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SBM1040CT-13-F Payment Methods





If you have any question about SBM1040CT-13-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com