

SBRT20M80SP5-13

SBRT20M80SP5-13 Information

Water fiels ener.com	 SBRT20M80SP5-13 Diodes Incorporated Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE SBR 80V 20A POWERDI5 PowerDI? 5 For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SBRT20M80SP5-13 Specifications

ManufacturerDiodes IncorporatedCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackagePowerDI? 5SeriesAutomotive, AEC-Q101Diode TypeSuper BarrierVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io)20AVoltage - Forward (Vf) (Max) @ If660mV @ 20ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 80VCapacitance @ Vr, FSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI? 5Operating Temperature - Junction-55°C ~ 150°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackagePowerDI? 5SeriesAutomotive, AEC-Q101Diode TypeSuper BarrierVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io)20AVoltage - Forward (Vf) (Max) @ If660mV @ 20ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	SBRT20M80SP5-13
Diodes - Rectifiers - SinglePackagePowerDI? 5SeriesAutomotive, AEC-Q101Diode TypeSuper BarrierVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io)20AVoltage - Forward (Vf) (Max) @ If660mV @ 20ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Manufacturer	Diodes Incorporated
PackagePowerDI? 5SeriesAutomotive, AEC-Q101Diode TypeSuper BarrierVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io)20AVoltage - Forward (Vf) (Max) @ If660mV @ 20ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series Automotive, AEC-Q101 Diode Type Super Barrier Voltage - DC Reverse (Vr) (Max) 80V Current - Average Rectified (Io) 20A Voltage - Forward (Vf) (Max) @ If 660mV @ 20A Speed Standard Recovery >500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 200μA @ 80V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case PowerDI? 5 Supplier Device Package PowerDI?5 Operating Temperature - Junction -55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeSuper BarrierVoltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io)20AVoltage - Forward (Vf) (Max) @ If660mV @ 20ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI? 50°COperating Temperature - Junction-55°C ~ 150°C	Package	PowerDI? 5
Voltage - DC Reverse (Vr) (Max)80VCurrent - Average Rectified (Io)20AVoltage - Forward (Vf) (Max) @ If660mV @ 20ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Series	Automotive, AEC-Q101
Current - Average Rectified (Io)20AVoltage - Forward (Vf) (Max) @ If660mV @ 20ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Diode Type	Super Barrier
Voltage - Forward (Vf) (Max) @ If $660mV @ 20A$ SpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $200\muA @ 80V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	80V
SpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	20A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200μA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	660mV @ 20A
Current - Reverse Leakage @ Vr200μA @ 80VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Speed	Standard Recovery >500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	200µA @ 80V
Package / CasePowerDI? 5Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device PackagePowerDI?5Operating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Package / Case	PowerDI? 5
	Supplier Device Package	PowerDI?5
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

SBRT20M80SP5-13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SBRT20M80SP5-13 Payment Methods



SBRT20M80SP5-13 Shipping Methods



If you have any question about SBRT20M80SP5-13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com