



SCB73F-3R3 Information

Isa

For Reference Only

Part Number SCB73F-3R3

Manufacturer Signal Transformer

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 3.3UH 3.8A 45 MOHM SMD

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SCB73F-3R3 Specifications

ManufacturerSignal TransformerCategoryInductors, Coils, ChokesFixed InductorsPackageNonstandardSeriesSCB73FTypeWirewoundMaterial - Core-Inductance3.3μHTolerance±20%Current Rating3.8ACurrent - Saturation2.08AShieldingUnshieldedDC Resistance (DCR)45 mOhm MaxQ @ Freq-Frequency - Self Resonant-Ratings-	
Fixed Inductors	
Package Nonstandard Series SCB73F Type Wirewound Material - Core - Inductance 3.3μH Tolerance ±20% Current Rating 3.8A Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Series SCB73F Type Wirewound Material - Core - Inductance 3.3μH Tolerance ±20% Current Rating 3.8A Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Type Wirewound Material - Core - Inductance 3.3μH Tolerance ±20% Current Rating 3.8A Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Material - Core - Inductance 3.3μH Tolerance ±20% Current Rating 3.8A Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Inductance 3.3μH Tolerance ±20% Current Rating 3.8A Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Tolerance ±20% Current Rating 3.8A Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Current Rating 3.8A Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Current - Saturation 2.08A Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
Shielding Unshielded DC Resistance (DCR) 45 mOhm Max Q @ Freq - Frequency - Self Resonant -	
DC Resistance (DCR) Q @ Freq Frequency - Self Resonant - 45 mOhm Max - -	
Q @ Freq - Frequency - Self Resonant -	
Frequency - Self Resonant -	
Ratings -	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Frequency - Test 1kHz	
Features -	
Mounting Type Surface Mount	
Package / Case Nonstandard	
Supplier Device Package -	
Size / Dimension 0.291" L x 0.291" W (7.40mm x 7.40mm)	

Height - Seated (Max)	0.138" (3.50mm)
	Report errors?

SCB73F-3R3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SCB73F-3R3 Payment Methods





















SCB73F-3R3 Shipping Methods













If you have any question about SCB73F-3R3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com