



SCEP134S-6R4 Information



For Reference Only

Part Number SCEP134S-6R4

Manufacturer Signal Transformer

Category Inductors, Coils, Chokes
Fixed Inductors

Description FIXED IND 6.4UH 8.5A 16.3 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SCEP134S-6R4 Specifications

Manufacturer Signal Transformer Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series SCEP134S Type - Material - Core - Inductance 6.4μH Tolerance ±20% Current Rating 8.5A Current - Saturation 8A Shielded DC Resistance (DCR) DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Sumplier Device Package -	Manufacturer Part Number	SCEP134S-6R4
Fixed Inductors	Manufacturer	Signal Transformer
Package Nonstandard Series SCEP134S Type - Material - Core - Inductance 6.4μH Tolerance ±20% Current Rating 8.5A Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Category	Inductors, Coils, Chokes
Series SCEP134S Type - Material - Core - Inductance 6.4µH Tolerance ±20% Current Rating 8.5A Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard		Fixed Inductors
Type - Material - Core - Inductance 6.4μH Tolerance ±20% Current Rating 8.5A Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Package	Nonstandard
Material - Core - Inductance 6.4μH Tolerance ±20% Current Rating 8.5A Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Series	SCEP134S
Inductance 6.4μH Tolerance ±20% Current Rating 8.5A Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Туре	-
Tolerance ±20% Current Rating 8.5A Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Material - Core	-
Current Rating 8.5A Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Inductance	6.4µH
Current - Saturation 8A Shielding Shielded DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Tolerance	±20%
Shielding DC Resistance (DCR) 16.3 mOhm Max Q @ Freq - Frequency - Self Resonant Ratings Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Shielded 16.3 mOhm Max - 100kmax - Surface Mount Nonstandard	Current Rating	8.5A
DC Resistance (DCR) Q @ Freq Frequency - Self Resonant Ratings Operating Temperature Frequency - Test Frequency - Test Mounting Type Surface Mount Package / Case 16.3 mOhm Max - 16.3 mOhm Max - 10.3 mOhm Max - 10.4 model	Current - Saturation	8A
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Shielding	Shielded
Frequency - Self Resonant Ratings Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features Mounting Type Surface Mount Package / Case Nonstandard	DC Resistance (DCR)	16.3 mOhm Max
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Q @ Freq	-
Operating Temperature -40°C ~ 125°C Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Frequency - Self Resonant	-
Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard	Frequency - Test	100kHz
Package / Case Nonstandard	Features	-
-	Mounting Type	Surface Mount
Supplier Device Package	Package / Case	Nonstandard
Supplier Beries Luciage	Supplier Device Package	-
Size / Dimension 0.547" L x 0.547" W (13.90mm x 13.90mm)	Size / Dimension	0.547" L x 0.547" W (13.90mm x 13.90mm)

Height - Seated (Max) 0.193" (4.90mm) Report errors?

SCEP134S-6R4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SCEP134S-6R4 Payment Methods



















SCEP134S-6R4 Shipping Methods













If you have any question about SCEP134S-6R4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com