

SCRH127-270 Information



For Reference Only

Part Number SCRH127-270

Manufacturer Signal Transformer

Category Inductors, Coils, Chokes
Fixed Inductors

Description FIXED IND 27UH 3.6A 45.9 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SCRH127-270 Specifications

Manufacturer Signal Transformer Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series SCRH127 Type - Material - Core - Inductance 27µH Tolerance ±20% Current Rating 3.6A Current - Saturation 3.4A Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - Size / Dimension 0.492" L x 0.492" W (12.50mm x 12.50mm)	Manufacturer Part Number	SCRH127-270
Fixed Inductors Package Nonstandard Series SCRH127 Type - Material - Core - Inductance 27μH Tolerance ±20% Current Rating 3.6A Current - Saturation 3.4A Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Manufacturer	Signal Transformer
PackageNonstandardSeriesSCRH127Type-Material - Core-Inductance27μHTolerance±20%Current Rating3.6ACurrent - Saturation3.4AShieldingShieldedDC Resistance (DCR)45.9 mOhm MaxQ @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-40°C ~ 125°CFrequency - Test1kHzFeatures-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Category	Inductors, Coils, Chokes
Series SCRH127 Type - Material - Core - Inductance 27μH Tolerance ±20% Current Rating 3.6A Current - Saturation 3.4A Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -		Fixed Inductors
Type - Material - Core - Inductance 27μH Tolerance ±20% Current Rating 3.6A Current - Saturation 3.4A Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Package	Nonstandard
Material - Core-Inductance $27\mu H$ Tolerance $\pm 20\%$ Current Rating $3.6A$ Current - Saturation $3.4A$ ShieldingShieldedDC Resistance (DCR) 45.9 mOhm Max Q @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Frequency - Test 1kHz Features-Mounting TypeSurface MountPackage / CaseNonstandardSupplier Device Package-	Series	SCRH127
Inductance 27µH Tolerance ±20% Current Rating 3.6A Current - Saturation 3.4A Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Туре	-
Tolerance ±20% Current Rating 3.6A Current - Saturation 3.4A Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Material - Core	-
Current Rating Current - Saturation 3.4A Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test IkHz Features Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package	Inductance	27μΗ
Current - Saturation Shielding Shielded DC Resistance (DCR) 45.9 mOhm Max Q @ Freq Frequency - Self Resonant Ratings Operating Temperature Frequency - Test IkHz Features Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package - Shielded 45.9 mOhm Max - C 40°C ~ 125°C IkHz Frequency - Test IkHz Features - C Mounting Type Surface Mount Nonstandard Supplier Device Package	Tolerance	±20%
Shielding DC Resistance (DCR) 45.9 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Supplier Device Package -	Current Rating	3.6A
DC Resistance (DCR) Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test Frequency - Test Mounting Type Surface Mount Package / Case Supplier Device Package - 45.9 mOhm Max 45.9 mOhm Max 45.9 mOhm Max - 40°C ~ 125°C 1kHz 5urface Mount Nonstandard Nonstandard - Supplier Device Package	Current - Saturation	3.4A
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Shielding	Shielded
Frequency - Self Resonant Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test IkHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	DC Resistance (DCR)	45.9 mOhm Max
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Q @ Freq	-
Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Self Resonant	-
Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard Supplier Device Package -	Frequency - Test	1kHz
Package / Case Nonstandard Supplier Device Package -	Features	-
Supplier Device Package -	Mounting Type	Surface Mount
	Package / Case	Nonstandard
Size / Dimension 0.492" L x 0.492" W (12.50mm x 12.50mm)	Supplier Device Package	-
	Size / Dimension	0.492" L x 0.492" W (12.50mm x 12.50mm)

Height - Seated (Max) 0.315" (8.00mm) Report errors?

SCRH127-270 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SCRH127-270 Payment Methods



















SCRH127-270 Shipping Methods













If you have any question about SCRH127-270, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com