



SCRH2D14-3R3 Information

See

For Reference Only

Part Number SCRH2D14-3R3

Manufacturer Signal Transformer

Category Inductors, Coils, Chokes
Fixed Inductors

Description FIXED IND 3.3UH 1.15A 125 MOHM

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SCRH2D14-3R3 Specifications

ManufacturerSignal TransformerCategoryInductors, Coils, ChokesFixed InductorsPackageNonstandardSeriesSCRH2D14Type-Material - Core-Inductance3.3μHTolerance±30%Current Rating1.15ACurrent - Saturation1.2AShieldingShieldedDC Resistance (DCR)125 mOhm Max	
Fixed Inductors Package Nonstandard Series SCRH2D14 Type - Material - Core - Inductance 3.3μH Tolerance ±30% Current Rating 1.15A Current - Saturation 1.2A Shielding Shielded	
Package Nonstandard Series SCRH2D14 Type - Material - Core - Inductance 3.3μH Tolerance ±30% Current Rating 1.15A Current - Saturation 1.2A Shielding Shielded	
Series SCRH2D14 Type - Material - Core - Inductance 3.3μH Tolerance ±30% Current Rating 1.15A Current - Saturation 1.2A Shielding Shielded	
Type - Material - Core - Inductance 3.3μH Tolerance ±30% Current Rating 1.15A Current - Saturation 1.2A Shielding Shielded	
$\begin{array}{cccc} Material - Core & & - \\ Inductance & & 3.3 \mu H \\ Tolerance & & \pm 30\% \\ Current Rating & & 1.15A \\ Current - Saturation & & 1.2A \\ Shielding & Shielded \\ \end{array}$	
Inductance 3.3μH Tolerance ±30% Current Rating 1.15A Current - Saturation 1.2A Shielding Shielded	
Tolerance ±30% Current Rating 1.15A Current - Saturation 1.2A Shielding Shielded	
Current Rating 1.15A Current - Saturation 1.2A Shielding Shielded	
Current - Saturation 1.2A Shielding Shielded	
Shielding Shielded	
DC Resistance (DCR) 125 mOhm Max	
Q @ Freq -	
Frequency - Self Resonant -	
Ratings -	
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Frequency - Test 100kHz	
Features -	
Mounting Type Surface Mount	
Package / Case Nonstandard	
Supplier Device Package -	
Size / Dimension 0.126" L x 0.126" W (3.20mm x 3.20mm)	

Height - Seated (Max) 0.061" (1.55mm) Report errors?

SCRH2D14-3R3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SCRH2D14-3R3 Payment Methods



















SCRH2D14-3R3 Shipping Methods













If you have any question about SCRH2D14-3R3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com