

SCRH73-180 Information



For Reference Only

Part NumberSCRH73-180ManufacturerSignal TransformerCategoryInductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 18UH 1.2A 140 MOHM SMD

Package Nonstandard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









SCRH73-180 Specifications

Manufacturer Signal Transformer Category Inductors, Coils, Chokes Fixed Inductors Package Nonstandard Series SCRH73 Type - Material - Core - Inductance 18μH Tolerance ±20% Current Rating 1.2A Current - Saturation 1.2A Shielding Shielded DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Manufacturer Part Number	SCRH73-180
Fixed Inductors	Manufacturer	Signal Transformer
Package Nonstandard Series SCRH73 Type - Material - Core - Inductance 18μH Tolerance ±20% Current Rating 1.2A Current - Saturation 1.2A Shielding Shielded DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Category	Inductors, Coils, Chokes
Series SCRH73 Type - Material - Core - Inductance 18μH Tolerance ±20% Current Rating 1.2A Current - Saturation 1.2A Shielding Shielded DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard		Fixed Inductors
Type	Package	Nonstandard
Material - Core-Inductance $18\mu H$ Tolerance $\pm 20\%$ Current Rating $1.2A$ Current - Saturation $1.2A$ ShieldingShieldedDC Resistance (DCR) 140 mOhm Max Q @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Frequency - Test 1kHz Features-Mounting TypeSurface MountPackage / CaseNonstandard	Series	SCRH73
Inductance 18μH Tolerance ±20% Current Rating 1.2A Current - Saturation 1.2A Shielding Shielded DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Туре	-
Tolerance ±20% Current Rating 1.2A Current - Saturation 1.2A Shielding Shielded DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Material - Core	-
Current Rating 1.2A Current - Saturation 1.2A Shielding Shielded DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Inductance	18μΗ
Current - Saturation 1.2A Shielding Shielded DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Tolerance	±20%
Shielding DC Resistance (DCR) 140 mOhm Max Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test IkHz Features - Mounting Type Surface Mount Package / Case Shielded 140 mOhm Max - IkHz Frequency - Surface Mount Nonstandard	Current Rating	1.2A
DC Resistance (DCR) Q @ Freq Frequency - Self Resonant Ratings Operating Temperature Frequency - Test IkHz Features Mounting Type Surface Mount Package / Case 140 mOhm Max - 140 mOhm Max - 140 mOhm Max - Surface Mount Nonstandard	Current - Saturation	1.2A
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Shielding	Shielded
Frequency - Self Resonant Ratings Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features Mounting Type Surface Mount Package / Case Nonstandard	DC Resistance (DCR)	140 mOhm Max
Ratings - Operating Temperature -40°C ~ 125°C Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Q @ Freq	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Frequency - Self Resonant	-
Frequency - Test 1kHz Features - Mounting Type Surface Mount Package / Case Nonstandard	Ratings	-
Features - Mounting Type Surface Mount Package / Case Nonstandard	Operating Temperature	-40°C ~ 125°C
Mounting Type Surface Mount Package / Case Nonstandard	Frequency - Test	1kHz
Package / Case Nonstandard	Features	-
-	Mounting Type	Surface Mount
g 1' D ' D 1	Package / Case	Nonstandard
Supplier Device Package -	Supplier Device Package	-
Size / Dimension 0.307" L x 0.307" W (7.80mm x 7.80mm)	Size / Dimension	0.307" L x 0.307" W (7.80mm x 7.80mm)

Height - Seated (Max)	0.138" (3.50mm)
	Report errors?

SCRH73-180 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SCRH73-180 Payment Methods



















SCRH73-180 Shipping Methods













If you have any question about SCRH73-180, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com