

SCRN239R-F

equest a Quote

SCRN239R-F Information

	Part Number	SCRN239R-F	
www.heisener.com	Manufacturer	Cornell Dubilier Electronics (CDE)	
	Category	Capacitors Film Capacitors	ų,
	Description	CAP FILM 20UF 10% 1KVPK SCREW	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



SCRN239R-F Specifications

ManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsFilm CapacitorsPackageRadial, CanSeriesSCRCapacitance20µFTolerance±10%Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedOperating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560° L x 2.840° W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190° (131.83mm)TerminationScrew TerminalsLead Spacing000° (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures			
CategoryCapacitorsFilm CapacitorsPackageRadial, CanSeriesSCRCapacitance20µFTolerance±10%Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedSCR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketSize / Dimension5.190" (131.83mm)Height - Seated (Max)Screw TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	SCRN239R-F	
Film CapacitorsPackageRadial, CanSeriesSCRCapacitance20µFTolerance±10%Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560° L x 2.840° W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190° (131.83mm)TerminationScrew TerminalsLead Spacing2.000° (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Cornell Dubilier Electronics (CDE)	
PackageRadial, CanSeriesSCRCapacitance20μFTolerance±10%Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors	
SeriesSCRCapacitance20µFTolerance±10%Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension5.190" (131.83mm)Height - Seated (Max)Screw TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-		Film Capacitors	
Capacitance20μFTolerance±10%Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension5.190" (131.83mm)Height - Seated (Max)Screw TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial, Can	
Tolerance±10%Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)Applications-Features-	Series	SCR	
Voltage Rating - AC1000Vpk (1KVPK)Voltage Rating - DC-Dielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)Applications-	Capacitance	20µF	
Voltage Rating - DC-Dielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)Applications-Features-	Tolerance	±10%	
Dielectric MaterialPaper, MetallizedDielectric MaterialPaper, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	1000Vpk (1KVPK)	
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	-	
Operating Temperature-40°C ~ 80°CMounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Paper, Metallized	
Nounting TypeChassis Mount, Requires Holder/BracketPackage / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadial, CanSize / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 80^{\circ}\mathrm{C}$	
Size / Dimension4.560" L x 2.840" W (115.82mm x 72.14mm), LipHeight - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Chassis Mount, Requires Holder/Bracket	
Height - Seated (Max)5.190" (131.83mm)TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial, Can	
TerminationScrew TerminalsLead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	4.560" L x 2.840" W (115.82mm x 72.14mm), Lip	
Lead Spacing2.000" (50.80mm)ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	5.190" (131.83mm)	
ApplicationsCommutation; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	Screw Terminals	
Features -	Lead Spacing	2.000" (50.80mm)	
	Applications	Commutation; High Frequency, Switching; High Pulse, DV/DT	
Report errors?	Features	-	
			Report errors?

SCRN239R-F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

SCRN239R-F Payment Methods



SCRN239R-F Shipping Methods



If you have any question about SCRN239R-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com