

SCS603 Information

Part Number SCS603

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 3.3V 60W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









~~~~	~	_
SCS603	<b>Specificat</b>	ions

Manufacturer Part Number         SCS603           Manufacturer         TDK-Lambda Americas Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         SC60           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         SC60           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Manufacturer Part Number	SCS603
Package         -           Series         SC60           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package         -           Series         SC60           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         SC60           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Package	-
Number of Outputs         1           Voltage - Input         85 ~ 265 VAC           Voltage - Output 1         3.3V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         60W           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         70%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Series	SC60
Voltage - Input85 ~ 265 VACVoltage - Output 13.3VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)12APower (Watts)60WApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Type	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  - Efficiency  Operating Temperature  Power (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Size / Dimension  3.3V  3.3V  3.3V  3.3V  6.20  -  Current - Output (Max)  12A  6.0W  6	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  - Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Mounting Type  Chassis Mount  Size / Dimension  -  -  Current - Output (Max)  12A  60W  60W  Features  O°C ~ 70°C (With Derating)  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  - Efficiency  Operating Temperature  Peatures  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Current - Output (Max)  - Commercial)  - Chassis Mount  Size / Dimension  - Chassis Mount	Voltage - Output 1	3.3V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  70%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -  Current - Output (Max)  12A  -  12A  60W  (With Decay (Commercial)  60W  70%  Chassis Mount  60W  70%  70%  70%  70%  70%  70%  70%  7	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  70%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  12A  60W  Commercial  -  Commercia	Voltage - Output 3	-
Power (Watts) 60W  Applications ITE (Commercial)  Voltage - Isolation -  Efficiency 70%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation -  Efficiency 70%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Current - Output (Max)	12A
Voltage - Isolation  Efficiency 70%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Power (Watts)	60W
Efficiency 70%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Applications	ITE (Commercial)
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Voltage - Isolation	-
Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Efficiency	70%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Features	Adjustable Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)
		Report errors?

### **SCS603 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **SCS603 Payment Methods**



















# **SCS603 Shipping Methods**













If you have any question about SCS603, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com