

SCT68 Information

Part Number SCT68

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 15V 12V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









COTO	Chasifications
SCI08	Specifications

Manufacturer Part Number SCT68 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SC60 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm) Report errors?			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series SC60 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Manufacturer Part Number	SCT68	
Package - Series SC60 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Manufacturer	TDK-Lambda Americas Inc.	
Package - Series SC60 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series SC60 Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)		AC DC Converters	
Type Open Frame Number of Outputs 3 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Package	-	
Number of Outputs3Voltage - Input $85 \sim 265 \text{ VAC}$ Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4-Current - Output (Max) $7A, 3A, 920\text{mA}$ Power (Watts) 60W ApplicationsITE (Commercial)Voltage - Isolation-Efficiency 70% Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.34^{\circ}\text{H} (127.0\text{mm x } 76.2\text{mm x } 34.0\text{mm})$	Series	SC60	
Voltage - Input 85 ~ 265 VAC Voltage - Output 1 5V Voltage - Output 2 15V Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Type	Open Frame	
Voltage - Output 15VVoltage - Output 215VVoltage - Output 312VVoltage - Output 4-Current - Output (Max)7A, 3A, 920mAPower (Watts)60WApplicationsITE (Commercial)Voltage - Isolation-Efficiency70%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Number of Outputs	3	
Voltage - Output 2 Voltage - Output 3 12V Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 15V 12V -	Voltage - Input	85 ~ 265 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 12V - Current - Output (Max) - Commercial (Commercial) - Commercial (Commerci	Voltage - Output 1	5V	
Voltage - Output 4 Current - Output (Max) 7A, 3A, 920mA Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension - 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Voltage - Output 2	15V	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 7A, 3A, 920mA 60W Adjustable Output Features Adjustable Output Turiversal Input Chassis Mount 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Voltage - Output 3	12V	
Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation - Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Current - Output (Max)	7A, 3A, 920mA	
Voltage - Isolation Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Power (Watts)	60W	
Efficiency 70% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00 " L x 3.00 " W x 1.34 " H (127.0mm x 76.2 mm x 34.0 mm)	Applications	ITE (Commercial)	
Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Voltage - Isolation	-	
Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Efficiency	70%	
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Operating Temperature	0°C ~ 70°C (With Derating)	
Size / Dimension 5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	Features	Adjustable Output, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.34" H (127.0mm x 76.2mm x 34.0mm)	
			Report errors?

SCT68 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

SCT68 Payment Methods





















SCT68 Shipping Methods













If you have any question about SCT68, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com