



### **SCXL004DN Information**



For Reference Only

Part Number SCXL004DN

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRESSURE DIFF 4" H2O 6SIP

Package 6-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **SCXL004DN Specifications**

Manufacturer Part Number       SCXL004DN         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Sensors, Transducers         Package       6-SIP Module         Series       SCXL         Pressure Type       Differential         Operating Pressure       0.15 PSI (1 kPa)         Output Type       Wheatstone Bridge         Output       0 mV ~ 40 mV (12V)         Accuracy       ±1%         Voltage - Supply       18V         Port Size       Male - 0.19" (4.8mm) Tube, Dual         Port Style       Barbed         Features       Temperature Compensated         Termination Style       Surface Mount         Maximum Pressure       0.36 PSI (2.49 kPa)         Operating Temperature       0°C ~ 70°C         Package / Case       6-SIP Module         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackage6-SIP ModuleSeriesSCXLPressure TypeDifferentialOperating Pressure0.15 PSI (1 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 40 mV (12V)Accuracy±1%Voltage - Supply18VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure0.36 PSI (2.49 kPa)Operating Temperature0°C ~ 70°CPackage / Case6-SIP ModuleSupplier Device Package-	Manufacturer Part Number	SCXL004DN
Package         6-SIP Module           Series         SCXL           Pressure Type         Differential           Operating Pressure         0.15 PSI (1 kPa)           Output Type         Wheatstone Bridge           Output         0 mV ~ 40 mV (12V)           Accuracy         ±1%           Voltage - Supply         18V           Port Size         Male - 0.19" (4.8mm) Tube, Dual           Port Style         Barbed           Features         Temperature Compensated           Termination Style         Surface Mount           Maximum Pressure         0.36 PSI (2.49 kPa)           Operating Temperature         0°C ~ 70°C           Package / Case         6-SIP Module           Supplier Device Package         -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package6-SIP ModuleSeriesSCXLPressure TypeDifferentialOperating Pressure0.15 PSI (1 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 40 mV (12V)Accuracy±1%Voltage - Supply18VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure0.36 PSI (2.49 kPa)Operating Temperature0°C ~ 70°CPackage / Case6-SIP ModuleSupplier Device Package-	Category	Sensors, Transducers
SeriesSCXLPressure TypeDifferentialOperating Pressure0.15 PSI (1 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 40 mV (12V)Accuracy±1%Voltage - Supply18VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure0.36 PSI (2.49 kPa)Operating Temperature0°C ~ 70°CPackage / Case6-SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure 0.15 PSI (1 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 40 mV (12V) Accuracy ±1% Voltage - Supply 18V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.36 PSI (2.49 kPa) Operating Temperature 0°C ~ 70°C Package / Case 6-SIP Module Supplier Device Package	Package	6-SIP Module
Operating Pressure Output Type Wheatstone Bridge Output Output On W ~ 40 mV (12V) Accuracy ±1% Voltage - Supply 18V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbed Features Temperature Compensated Termination Style Surface Mount Maximum Pressure O36 PSI (2.49 kPa) Operating Temperature Por C ~ 70°C Package / Case Supplier Device Package  -  O.15 PSI (1 kPa) One Wheatstone Bridge Wheatstone Bridge Wheatstone Bridge Velaw (1.2V) Accuracy And Mav (12V) Accuracy And Mav (12V) Accuracy And Mav (12V) Accuracy Accu	Series	SCXL
Output TypeWheatstone BridgeOutput0 mV ~ 40 mV (12V)Accuracy±1%Voltage - Supply18VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure0.36 PSI (2.49 kPa)Operating Temperature0°C ~ 70°CPackage / Case6-SIP ModuleSupplier Device Package-	Pressure Type	Differential
Output 0 mV ~ 40 mV (12V)  Accuracy ±1%  Voltage - Supply 18V  Port Size Male - 0.19" (4.8mm) Tube, Dual  Port Style Barbed  Features Temperature Compensated  Termination Style Surface Mount  Maximum Pressure 0.36 PSI (2.49 kPa)  Operating Temperature 0°C ~ 70°C  Package / Case 6-SIP Module  Supplier Device Package	Operating Pressure	0.15 PSI (1 kPa)
Accuracy ±1%  Voltage - Supply 18V  Port Size Male - 0.19" (4.8mm) Tube, Dual  Port Style Barbed  Features Temperature Compensated  Termination Style Surface Mount  Maximum Pressure 0.36 PSI (2.49 kPa)  Operating Temperature 0°C ~ 70°C  Package / Case 6-SIP Module  Supplier Device Package -	Output Type	Wheatstone Bridge
Voltage - Supply18VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarbedFeaturesTemperature CompensatedTermination StyleSurface MountMaximum Pressure0.36 PSI (2.49 kPa)Operating Temperature0°C ~ 70°CPackage / Case6-SIP ModuleSupplier Device Package-	Output	$0 \text{ mV} \sim 40 \text{ mV} (12\text{V})$
Port Size Male - 0.19" (4.8mm) Tube, Dual  Port Style Barbed  Features Temperature Compensated  Termination Style Surface Mount  Maximum Pressure 0.36 PSI (2.49 kPa)  Operating Temperature 0°C ~ 70°C  Package / Case 6-SIP Module  Supplier Device Package -	Accuracy	±1%
Port Style Barbed  Features Temperature Compensated  Termination Style Surface Mount  Maximum Pressure 0.36 PSI (2.49 kPa)  Operating Temperature 0°C ~ 70°C  Package / Case 6-SIP Module  Supplier Device Package -	Voltage - Supply	18V
Features Temperature Compensated Termination Style Surface Mount Maximum Pressure 0.36 PSI (2.49 kPa) Operating Temperature 0°C ~ 70°C Package / Case 6-SIP Module Supplier Device Package -	Port Size	Male - 0.19" (4.8mm) Tube, Dual
Termination Style  Surface Mount  Maximum Pressure  0.36 PSI (2.49 kPa)  Operating Temperature  0°C ~ 70°C  Package / Case  6-SIP Module  Supplier Device Package	Port Style	Barbed
Maximum Pressure0.36 PSI (2.49 kPa)Operating Temperature0°C ~ 70°CPackage / Case6-SIP ModuleSupplier Device Package-	Features	Temperature Compensated
Operating Temperature0°C ~ 70°CPackage / Case6-SIP ModuleSupplier Device Package-	Termination Style	Surface Mount
Package / Case 6-SIP Module Supplier Device Package -	Maximum Pressure	0.36 PSI (2.49 kPa)
Supplier Device Package -	Operating Temperature	0°C ~ 70°C
	Package / Case	6-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

### **SCXL004DN Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **SCXL004DN Payment Methods**





















### **SCXL004DN Shipping Methods**













If you have any question about SCXL004DN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com